

Huang Liang 1.85 mm Male to SMA Female Adapter

SKU: ACC-HL-00003
 MPN: ADU1-VM1-SMF1

Description

The Huang Liang 1.85 mm Male to SMA Female Adapter (Part Number: ADU1-VM1-SMF1) is a high-quality 50 Ω coaxial RF adapter. Designed and manufactured in Taiwan, this adapter features a 1.85 mm Male interface with a straight, free-hanging body compatible with 1.85 mm Female and 2.4 mm Female interfaces. The SMA Female interface, also straight and free-hanging, is compatible with SMA Male connectors.

The adapter supports an operating frequency range from 0 GHz to 26.5 GHz, ensuring broad applicability across various RF systems. It is constructed from durable stainless steel (303) with a passivated finish for enhanced corrosion resistance. The inner contacts are made of beryllium copper and gold-plated for excellent conductivity and reliability.

With an operating temperature range of -40 °C to 105 °C, this adapter is suitable for a wide range of environmental conditions. Certified to ISO 9001 standards and RoHS compliant, it meets rigorous...

[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
1.85 mm Male	Straight	Free Hanging
SMA Female	Straight	Free Hanging

RF Specification



Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	26.5 GHz	Inner Contact Resistance:	≤ 6 mΩ
RF Operating Voltage:	≥ 325 Vrms	Insulation Resistance:	≥ 3000 mΩ
		Outer Contact Resistance:	≤ 2 mΩ

VSWR Measurement


Frequency	VSWR	Insertion Loss
26500 MHz	≤ 1.2:1	0.3 dB

Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-40 °C
Weight:	5.4 g	Max. Operating Temperature:	105 °C
Compliance/Certifications:	ISO 9001 Quality Management	Mating Cycles:	> 500

RoHS

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

