Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Huang Liang 2.4 mm Male to 2.4 mm Female Adapter

SKU
ACC-HL-00028
MPN
ADU2-QM1-QF1

Description

The Huang Liang 2.4 mm Male to 2.4 mm Female Adapter (Part Number: ADU2-QM1-QF1) is a high-quality 50 Ω coaxial RF adapter. It features a 2.4 mm Male straight body interface, compatible with 2.4 mm Male and 1.85 mm Female connections, and a 2.4 mm Female straight body interface, compatible with 2.4 mm Male and 1.85 mm Male connections. The adapter's operating frequency range is from 0 GHz to 50 GHz, making it suitable for a wide range of RF applications.

Constructed from stainless steel (303) with a passivated finish, the adapter ensures durability and resistance to corrosion. The inner contacts are made of beryllium copper with gold plating, ensuring reliable and high-performance electrical connections. It operates effectively in temperatures ranging from -40 °C to 105 °C.

Manufactured to ISO 9001 quality management standards and compliant with RoHS directives, this adapter guarantees quality and environmental safety. Huang Liang, based...

Read More



Huang Liang
TECHNOLOGIES CO., LTD.

Huang Liang

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

RF Interface	Body Shape	Mounting
2.4 mm Male	Straight	Free Hanging
2.4 mm Female	Straight	Free Hanging

RF Specification

Start Frequency
0 GHz
Stop Frequency
50 GHz
RF Operating Voltage
≥ 250 Vrms
Input Impedance
50 Ω
Inner Contact Resistance
≤ 6 mΩ
Insulation Resistance
≥ 3000 mΩ
Outer Contact Resistance

≤ 2 mΩ

VSWR Measurement

Frequency	VSWR	Insertion Loss
50000 MHz	≤ 1.25:1	0.42 dB

Physical Specification

Body Material

Stainless Steel (303)

Body Plating

Passivated

Insulator Material

PTFE / Teflon

Weight

7.3 g

Compliance/Certifications

ISO 9001 Quality Management

,

RoHS

Contact Material

Beryllium Copper

Contact Plating

Gold

Min. Operating Temperature

-40 °C

Max. Operating Temperature


105 °C

Mating Cycles

> 500

Drawing

Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

