

Huang Liang 2.4 mm Male to 2.4 mm Male Adapter

SKU: ACC-HL-00029
 MPN: ADU2-QM1-QM1

Description

The Huang Liang ADU2-QM1-QM1 is a 2.4 mm Male to 2.4 mm Male Adapter designed for high-frequency RF applications, operating from 0 GHz to 50 GHz. This 50 Ω coaxial RF adapter features a straight-body, free-hanging mounting mechanism, compatible with 2.4 mm Male and 1.85 mm Female connectors.

Constructed from Stainless Steel (303) with a passivated finish for durability, the inner contacts are made of Beryllium Copper with Gold plating, ensuring optimal conductivity. It operates efficiently within a temperature range of -40 °C to 105 °C.

Manufactured in compliance with ISO 9001 and RoHS standards, this adapter guarantees high quality and reliability. Huang Liang, a Taiwanese company with over 30 years of experience, is renowned for its precision in coaxial connectors, adapters, and cable assemblies, serving sectors like military, telecommunications, and aerospace.



RF Connector Interface

RF Interface	Body Shape	Mounting
2.4 mm Male	Straight	Free Hanging
2.4 mm Male	Straight	Free Hanging

RF Specification



Huang Liang

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	50 GHz	Inner Contact Resistance:	≤ 6 mΩ
RF Operating Voltage:	≥ 250 Vrms	Insulation Resistance:	≥ 3000 mΩ
		Outer Contact Resistance:	≤ 2 mΩ


VSWR Measurement

Frequency	VSWR	Insertion Loss
50000 MHz	≤ 1.25:1	0.42 dB

Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-40 °C
Weight:	7 g	Max. Operating Temperature:	105 °C
Compliance/Certifications:	ISO 9001 Quality Management	Mating Cycles:	> 500
RoHS			

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

