

Huang Liang 1.85 mm Female to 2.4 mm Female Adapter

SKU: ACC-HL-00019
MPN: ADU2-VF1-QF1

Description

The Huang Liang 1.85 mm Female to 2.4 mm Female Adapter (Part Number: ADU2-VF1-QF1) is a high-quality, 50 Ω coaxial RF adapter from Taiwan-based Huang Liang. This adapter features a 1.85 mm Female interface and a 2.4 mm Female interface, both with a straight body shape and free-hanging mounting mechanism. It supports 1.85 mm and 2.4 mm Male interfaces, making it versatile for various applications.

Operating within a frequency range of 0 GHz to 50 GHz, this adapter is constructed from Stainless Steel (303) with a passivated finish for durability. The inner contacts are made of Beryllium Copper, plated with Gold, ensuring excellent conductivity and corrosion resistance. It can function effectively in temperatures ranging from -40 °C to 105 °C.

Compliant with ISO 9001 Quality Management standards and RoHS, the adapter guarantees reliability and safety. Huang Liang, with over 30 years of expertise in RF technology, provides precision coaxial...

[Read More](#)



Huang Liang

Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

RF Connector Interface

RF Interface	Body Shape	Mounting
1.85 mm Female	Straight	Free Hanging
2.4 mm Female	Straight	Free Hanging

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	50 GHz	Inner Contact Resistance:	≤ 6 mΩ
RF Operating Voltage:	≥ 250 Vrms	Insulation Resistance:	≥ 3000 mΩ
		Outer Contact Resistance:	≤ 2 mΩ


VSWR Measurement

Frequency	VSWR	Insertion Loss
50000 MHz	≤ 1.25:1	0.42 dB

Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-40 °C
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	105 °C
RoHS		Mating Cycles:	> 500

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

