

# Huang Liang 1.85 mm Male to 2.4 mm Male Adapter

SKU: ACC-HL-00010  
 MPN: ADU2-VM1-QM1

## Description

The Huang Liang 1.85 mm Male to 2.4 mm Male Adapter (Part Number: ADU2-VM1-QM1) is a high-quality 50 Ω coaxial RF adapter designed for optimal performance in telecommunications, military, and aerospace applications. This adapter features a 1.85 mm Male interface and a 2.4 mm Male interface, both with a straight body shape and free-hanging mounting mechanism, ensuring compatibility with various female and male connectors.

Operating within a wide frequency range of 0 to 50 GHz, this adapter is constructed from durable Stainless Steel (303) with a passivated finish for corrosion resistance. The inner contacts are made of Beryllium Copper with Gold plating, ensuring excellent conductivity and reliability. It performs efficiently in temperatures ranging from -40 °C to 105 °C, making it suitable for diverse environmental conditions.

Huang Liang, a Taiwanese manufacturer with over 30 years of experience, adheres to ISO 9001 Quality Management...

[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
1.85 mm Male	Straight	Free Hanging
2.4 mm Male	Straight	Free Hanging

## RF Specification



Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	50 GHz	Inner Contact Resistance:	≤ 6 mΩ
RF Operating Voltage:	≥ 250 Vrms	Insulation Resistance:	≥ 3000 mΩ
		Outer Contact Resistance:	≤ 2 mΩ

VSWR Measurement


Frequency	VSWR	Insertion Loss
50000 MHz	≤ 1.25:1	0.42 dB

## Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-40 °C
Weight:	6.9 g	Max. Operating Temperature:	105 °C
Compliance/Certifications:	ISO 9001 Quality Management	Mating Cycles:	> 500

RoHS

# Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

