

Zetifi 4G-5G Cellular Smart Antenna Black, 698 to 3800 MHz, 1050mm

SKU: ANT-ZT-00001

MPN: ANCA1101AU-02

Description

Welcome to a true revolution in antenna technology - a location-aware variable gain antenna that automatically switches between high and low gain modes to deliver peak performance in every setting.

Powered by our innovative ZetiLink technology, the antenna automatically selects the optimal gain mode for your device based on a blend of GPS location that is used to categorise your location as flat or hilly, antenna attitude (tilt), and user-selected preferences.

Get more out of your signal repeater or cellular gateway device with the convenience and enhanced performance of a Zetifi smart antenna.

- Reconfigurable antenna whip provides high and low gain modes in a single antenna
- Inbuilt GPS sensor linked to ZetiLink data set identifies terrain as flat, hilly or urban
- Gyroscope detects antenna attitude (tilt) to adjust gain for road gradient.
- ZetiLink engine processes location and other data in real-time to determine optimal gain mode.



RF Specification

Zetifi

Low Gain Mode

Zetifi was founded in 2017 to overcome the unique connectivity challenges faced by farmers and rural residents. The company's regional base in Wagga Wagga, Australia, on the doorstep of one of Australia's most productive agricultural regions, allows Zetifi to consult closely with primary producers and agribusiness stakeholders as they develop their technology and solutions.

Start Frequency: 698 MHz Polarisation: Vertical (V)

Stop Frequency: 3800 MHz Input Impedance: 50

Frequency Test Data

| Start Freq. | Stop Freq. | Peak Gain | VSWR | Azimuth | Elevation |
|-------------|------------|-----------|---------|---------|-----------|
| 698 MHz | 900 MHz | 3 dBi | < 2.5:1 | 360° | 50° |
| 1710 MHz | 2700 MHz | 3 dBi | < 2.1:1 | 360° | 30° |
| 3400 MHz | 3800 MHz | 3 dBi | < 2.1:1 | 360° | 20° |

High Gain Mode

Start Frequency: 698 MHz Polarisation: Vertical (V)

Stop Frequency: 3800 MHz Input Impedance: 50

Frequency Test Data

| Start Freq. | Stop Freq. | Peak Gain | VSWR | Azimuth | Elevation |
|-------------|------------|-----------|---------|---------|-----------|
| 698 MHz | 900 MHz | 6.5 dBi | < 2.5:1 | 360° | 25° |
| 1710 MHz | 2700 MHz | 6.5 dBi | < 2.1:1 | 360° | 15° |
| 3400 MHz | 3800 MHz | 6.5 dBi | < 2.1:1 | 360° | 10° |

Physical Specification

| | | | |
|--------------|-----------|-------------|-------------------------|
| Subtype: | Collinear | Dimensions: | 1050 x 56 mm (L x Dia) |
| Input Ports: | 1 | Materials: | Fibreglass (GRP), Steel |
| MIMO: | 1x1 SISO | Weight: | 2 kg |

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

