

# Skywave 4G-5G Vehicle Bullbar Antenna, 698 to 2200 MHz, SMA Male

SKU: ANT-SK-00001  
 MPN: VVCL-6922-5

## Description

The Skywave 5G Bullbar Antenna has been engineered for the highest possible performance on regional and rural 4G-5G networks. It sports a massive heavy-duty stainless-steel bell-spring for rough corrugations and thick fibreglass whip. Its tapered 27-32 mm fibreglass tube supports a wide PCB radiator which delivers maximum connectivity range with a total height of only 830 mm. We've gone wider not taller.

For serious endurance we've built the removable whip using an IP67 rated 4.3-10 interface, that isolates mechanical stresses from the RF connection, meaning even the harshest outback tracks won't stress the conductor.

Tuned for maximum performance on 4G Band 28 (700 MHz), 5G Band 26 (850 MHz), and 5G Band 8 (900 MHz) the antenna is able to achieve the best possible performance in areas where connectivity really counts. The antenna also supports mid-band frequencies with good performance to 2200 MHz, and unity performance out to 3800 MHz ...

[Read More](#)



## RF Specification

|                   |          |                  |              |
|-------------------|----------|------------------|--------------|
| Start Frequency:  | 698 MHz  | Polarisation:    | Vertical (V) |
| Stop Frequency:   | 2200 MHz | Input Impedance: | 50 Ω         |
| Max. Input Power: | 10 W     |                  |              |

RF Connectors

| Ports | RF Interface | Body Shape | Cable Series | Length  |
|-------|--------------|------------|--------------|---------|
| 1     | SMA Male     | Straight   | RG-58        | 5000 mm |


Frequency Test Data

| Start Freq. | Stop Freq. | Peak Gain | VSWR    | Azimuth | Elevation | Efficiency |
|-------------|------------|-----------|---------|---------|-----------|------------|
| 723 MHz     | 723 MHz    | 5.2 dBi   | < 1.2:1 | 360°    | 41°       | 61%        |
| 778 MHz     | 778 MHz    | 5.2 dBi   | < 1.2:1 | 360°    | 36°       | 55%        |
| 840 MHz     | 840 MHz    | 5.2 dBi   | < 1.6:1 | 360°    | 35°       | 56%        |
| 885 MHz     | 885 MHz    | 5.25 dBi  | < 1.8:1 | 360°    | 37°       | 53%        |
| 911 MHz     | 911 MHz    | 5.6 dBi   | < 1.9:1 | 360°    | 37°       | 47%        |
| 956 MHz     | 956 MHz    | 5.4 dBi   | < 1.2:1 | 360°    | 25°       | 42%        |
| 1710 MHz    | 1710 MHz   | 2 dBi     | < 2:1   | 360°    |           | 16%        |
| 1880 MHz    | 1880 MHz   | 2.4 dBi   | < 2.4:1 | 360°    |           | 16%        |
| 2170 MHz    | 2170 MHz   | 5.5 dBi   | < 2.4:1 | 360°    |           | 18%        |

# Physical Specification

|                             |           |                            |                                       |
|-----------------------------|-----------|----------------------------|---------------------------------------|
| Subtype:                    | Collinear | Materials:                 | Fibreglass (GRP)                      |
| Input Ports:                | 1         | Weight:                    | 1.5 kg                                |
| MIMO:                       | 1x1 SISO  | Compliance/Certifications: | ISO 9001 Quality Management           |
| Min. Operating Temperature: | -40 °C    | Mechanical Compliance:     | MIL-STD-810: Environmental Durability |
| Max. Operating Temperature: | 85 °C     |                            |                                       |

# Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

