

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# CommScope78EZNM Type N Male EZfit(r) for 7/8 in FXL-780, AVA5-50, and AVA5-50FX cable

SKU: ACC-CS-00010 MPN: 78EZNM

## Description

The CommScope 78EZNM Type N Male EZfit® connector is designed for 7/8 in FXL-780, AVA5-50, and AVA5-50FX coaxial cables. This N Male connector features a straight body and free-hanging mounting style, employing a captivated attachment mechanism for reliable connections. With dimensions of 57.91 x 37.08 mm and a weight of 152.89 g, it is robustly constructed with a silver-plated body and inner contacts, ensuring durability through more than 500 mating cycles.

Operating efficiently within a temperature range of -40 °C to 85 °C, the connector supports frequencies up to 5000 GHz while maintaining a 3rd Order PIM rating of  $\leq$  -116 dBc. It offers an input impedance of 50  $\Omega$ , inner contact resistance of  $\leq$  2 m $\Omega$ , and insulation resistance of  $\geq$  5000 m $\Omega$ . The connector can handle peak power up to 10000 kW and an RF operating voltage of  $\leq$  707 Vrms.

Compliant with ISO 9001 Quality Management and RoHS certifications, the 78EZNM has been tested to meet IEC...

Read More



#### CommScope

**COMMSCOPE®** 

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

## RF Connector Interface

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging

# RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	5000 GHz	Inner Contact Resistance:	≤ 2 mΩ
Peak Power:	10000 kW	Insulation Resistance:	≥ 5000 mΩ
PIM, 3rd Order:	≤ -116 dBc	Outer Contact Resistance:	≤ 0.3 mΩ
		RF Operating Voltage:	≤ 707 Vrms

## **VSWR** Measurement

Frequency	VSWR	Return Loss	Insertion Loss
50 MHz	≤ 1.02:1	≤ 40.09 dB	0.05 dB
1000 MHz	≤ 1.03:1	≤ 38.17 dB	
1900 MHz	≤ 1.04:1	≤ 35.05 dB	

## **Physical Specification**

Cable Group:	7/8 Corrugated	Conductor Attachment:	Cable, Captivated
Dimensions:	57.91 x 37.08	Contact Plating:	Silver
Weight:	152.89 g	Min. Operating Temperature:	-40 °C
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	85 °C
RoHS	,	Ingress Protection:	IP68
Mechanical Compliance:	IEC 60068-2-6: Vibration	Mating Cycles:	> 500

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

