

CommScope F4PNMV2-HC Type N Male for 1/2 in FSJ4-50B cable

SKU: ACC-CS-00114
 MPN: F4PNMV2-HC

Description

The CommScope F4PNMV2-HC Type N Male connector is designed for 1/2 inch FSJ4-50B coaxial cables. This RF connector features a straight, free-hanging mounting style, ideal for seamless integration in various RF applications. Constructed from brass with a durable plating and gold-plated inner contacts, it ensures reliable performance and longevity. The PTFE/Teflon insulator supports high thermal stability, operating in temperatures from -55°C to 85°C, and guarantees over 500 mating cycles.

This connector operates across a frequency range from 0 GHz to 12 GHz, with a 3rd Order PIM rating of ≤ -110 dBc, ensuring minimal interference in signal transmission. It offers an input impedance of 50Ω , with inner and outer contact resistances of ≤ 0 m Ω , and an insulation resistance of ≥ 5000 m Ω . The connector supports a peak power of 10,000 kW and an RF operating voltage of ≤ 707 Vrms.

Performance metrics include a VSWR of $\leq 1.04:1$ and return loss of...

[Read More](#)

[RF Connector Interface](#)



RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging

CommScope

COMMSCOPE®
RF Specification

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	12000 GHz	Inner Contact Resistance:	$\leq 0 \text{ m}\Omega$
Peak Power:	10000 kW	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
PIM, 3rd Order:	$\leq -110 \text{ dBc}$	Outer Contact Resistance:	$\leq 0.3 \text{ m}\Omega$
		RF Operating Voltage:	$\leq 707 \text{ Vrms}$

VSWR Measurement

Frequency	VSWR	Return Loss	Insertion Loss
1000 MHz	$\leq 1.04:1$	$\leq 35.05 \text{ dB}$	0.05 dB
3000 MHz	$\leq 1.08:1$	$\leq 27.99 \text{ dB}$	0.05 dB

Physical Specification

Cable Group:	1/2 Corrugated	Conductor Attachment:	Cable, Captivated
Body Material:	Brass	Contact Material:	Brass
Insulator Material:	PTFE / Teflon	Contact Plating:	Gold
Dimensions:	54.1 x 24.13	Min. Operating Temperature:	-55 °C
Weight:	90.72 g	Max. Operating Temperature:	85 °C
Compliance/Certifications:	ISO 9001 Quality Management	Ingress Protection:	IP68
RoHS		Mating Cycles:	> 500
Mechanical Compliance:	IEC 60068-2-27: Mechanical Shock		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

