

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

CommScope F4HM-D 4.3-10 Male for 1/2 in FSJ4-50B cable

SKU: ACC-CS-00119 MPN: F4HM-D

Description

The CommScope F4HM-D 4.3-10 Male RF Connector, part number F4HM-D (SKU: ACC-CS-00119), is designed for 1/2 inch FSJ4-50B corrugated cables. This coaxial connector features a straight, free-hanging design and uses a captivated cable attachment mechanism. With dimensions of 62.48 x 24.89 mm and a weight of 100 g, its robust construction includes plated body and silver-plated inner contacts to ensure durability and high performance.

Engineered to withstand over 100 mating cycles, it operates within a temperature range of -55°C to 85°C and supports frequencies from 0 GHz to 7500 GHz. It boasts a third-order PIM rating of \leq -116 dBc, with an inner contact resistance of \leq 1 m Ω and an outer contact resistance of \leq 2 m Ω . The connector maintains a 50 Ω input impedance and an insulation resistance of \geq 5000 m Ω . Capable of handling a peak power of 23 kW and an RF operating voltage of \leq 884 Vrms, it meets ISO 9001 and RoHS standards and adheres to...

Read More



CommScope



CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Connector Interface

RF Interface	Body Shape	Mounting
4.3-10 Male	Straight	Free Hanging

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	7500 GHz	Inner Contact Resistance:	≤ 0.8 mΩ
Peak Power:	22.5 kW	Insulation Resistance:	≥ 5000 mΩ
PIM, 3rd Order:	≤ -116 dBc	Outer Contact Resistance:	≤ 1.5 mΩ
		RF Operating Voltage:	≤ 884 Vrms

VSWR Measurement

Frequency	VSWR	Return Loss	Insertion Loss
1000 MHz	≤ 1.02:1	≤ 40.09 dB	0.05 dB

Physical Specification

Cable Group:	1/2 Corrugated	Conductor Attachment:	Cable, Captivated
Dimensions:	62.48 x 24.89	Contact Plating:	Silver
Weight:	100 g	Min. Operating Temperature:	-55 °C
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	85 °C
RoHS	,	Ingress Protection:	IP68
Mechanical Compliance:	IEC 60068-2-11: Salt Mist	Mating Cycles:	> 100
JEC COOCO 2 27 Markaria (Charl	ı		

IEC 60068-2-27: Mechanical Shock

IEC 60068-2-6: Vibration

IEC 60068-2-14: Change of Temperature

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

