

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

RF Adapter, N Female to N Female

SKU
ACC-PT-00048
MPN
AD-N2N2

Description

The Powertec RF Adapter (SKU: ACC-PT-00048, Part No: AD-N2N2) is a high-quality N Female to N Female adapter, ideal for a variety of RF applications.

Constructed from durable brass with nickel plating, this adapter features inner contacts made of phosphor bronze with gold plating, ensuring superior conductivity and reliability. It uses a PTFE/Teflon insulator and is designed for over 500 mating cycles, offering exceptional durability.

Operating efficiently across a broad frequency range from 0 GHz to 6 GHz, the adapter maintains an impedance of 50 Ω and supports an RF operating voltage of ≥ 500 Vrms. It demonstrates minimal contact resistance, with inner contact at ≤ 3 m Ω and outer contact at ≤ 2 m Ω , ensuring optimal signal integrity. The adapter can withstand extreme temperatures, ranging from -65 °C to 165 °C.

Tested to meet rigorous MIL-STD-202 standards, the adapter is resilient to thermal shock, corrosion, vibration, shock, and...

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface Body Shape Mounting

N Female	Straight	Free Hanging
N Female	Straight	Free Hanging

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

RF Operating Voltage

≥ 500 Vrms

Input Impedance

50 Ω

Inner Contact Resistance

≤ 3 m Ω

Outer Contact Resistance

≤ 2 m Ω

VSWR Measurement

Frequency VSWR

6000 MHz ≤ 1.25:1

Physical Specification

Body Material

[Brass](#)

Body Plating

[Nickel](#)

Insulator Material

[PTFE / Teflon](#)

Dimensions

28

Contact Material

[Phosphor Bronze](#)

Contact Plating

[Gold](#)

Min. Operating Temperature

-65 °C

Max. Operating Temperature

165 °C

Mating Cycles

> 500

Mechanical Compliance

[MIL-STD-202: Thermal Shock](#)

,

[MIL-STD-202: Corrosion](#)

,

[MIL-STD-202: Vibration](#)

,


[MIL-STD-202: Shock](#)

,

[MIL-STD-202: Moisture Resistance](#)

Drawing

Image



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

