

CommScope Directional Coupler, 15 dB, 555-6000 MHz, 4.3-10 Female, -165 dBc

SKU: ACC-CS-00022

MPN: C-15-UW-43-AI6

Description

The CommScope Directional Coupler (SKU: ACC-CS-00022) offers reliable RF signal management with a coupling value of 15 dB, covering a frequency range from 555 MHz to 6000 MHz. Engineered with 4.3-10 Female connectors for both input and output, it ensures robust connectivity and minimal signal loss. This component is IP67 rated for superior ingress protection, making it suitable for challenging environments, with an operational temperature range of -35 °C to 85 °C.

The coupler features a low Passive Intermodulation (PIM) rating of -165 dBc and maintains a 50 Ω impedance, adhering to ISO 9001 quality standards. Performance specifications include a VSWR of 1.3:1 and insertion loss of 0.50 dB between 4900 and 6000 MHz, with inter-port isolation exceeding 28 dB. Between 2700 and 3800 MHz, it offers a VSWR of 1.3:1 and isolation > 33 dB, while frequencies from 555 to 2700 MHz and 3800 to 4900 MHz also maintain isolation > 33 dB.

CommScope, a...

[Read More](#)



RF Specification

Min. Frequency:	555 MHz	Input Impedance:	50
Max. Frequency:	6000 MHz	Max. Input Power:	300 W
Coupling / Split:	15 dB	PIM, 3rd Order:	-165 dBc

Port Matrix

Port Function	RF Interface
Input	4.3-10 Female
Output	4.3-10 Female

Frequency Test Data

Start Frequency	Stop Frequency	VSWR	Insertion Loss	Inter-Port Iso.
4900 MHz	6000 MHz	< 1.3:1	0.5 dB	> 28 dB
2700 MHz	3800 MHz	< 1.25:1		> 33 dB
555 MHz	2700 MHz	< 1.2:1		> 33 dB
3800 MHz	4900 MHz			> 33 dB

Physical Specification

Input Ports:	1	Min. Operating Temperature:	-35 °C
Output Ports:	2	Max. Operating Temperature:	85 °C
Subtype:	Directional Coupler	Compliance/Certifications:	ISO 9001 Quality Management
Ingress Protection:	IP67		
Dimensions:	159 x 72 x 22 mm		
Weight:	0.38 kg		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

