

CommScope Directional Coupler, 15 dB, 555-6000 MHz, 4.3-10 Female, -165 dBc

SKU: ACC-CS-00022

MPN: C-15-UW-43-A16

Description

The CommScope Directional Coupler (SKU: ACC-CS-00022) offers reliable RF signal management with a coupling value of 15 dB, covering a frequency range from 555 MHz to 6000 MHz. Engineered with 4.3-10 Female connectors for both input and output, it ensures robust connectivity and minimal signal loss. This component is IP67 rated for superior ingress protection, making it suitable for challenging environments, with an operational temperature range of -35 °C to 85 °C.

The coupler features a low Passive Intermodulation (PIM) rating of -165 dBc and maintains a 50 Ω impedance, adhering to ISO 9001 quality standards. Performance specifications include a VSWR of 1.3:1 and insertion loss of 0.50 dB between 4900 and 6000 MHz, with inter-port isolation exceeding 28 dB. Between 2700 and 3800 MHz, it offers a VSWR of 1.3:1 and isolation > 33 dB, while frequencies from 555 to 2700 MHz and 3800 to 4900 MHz also maintain isolation > 33 dB.

CommScope, a...

[Read More](#)



COMMScope®

CommScope

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Specification

| | | | |
|-------------------|----------|-------------------|----------|
| Min. Frequency: | 555 MHz | Input Impedance: | 50 |
| Max. Frequency: | 6000 MHz | Max. Input Power: | 300 W |
| Coupling / Split: | 15 dB | PIM, 3rd Order: | -165 dBc |

Port Matrix

| Port Function | RF Interface |
|---------------|---------------|
| Input | 4.3-10 Female |
| Output | 4.3-10 Female |

Frequency Test Data

| Start Frequency | Stop Frequency | VSWR | Insertion Loss | Inter-Port Iso. |
|-----------------|----------------|----------|----------------|-----------------|
| 4900 MHz | 6000 MHz | < 1.3:1 | 0.5 dB | > 28 dB |
| 2700 MHz | 3800 MHz | < 1.25:1 | | > 33 dB |
| 555 MHz | 2700 MHz | < 1.2:1 | | > 33 dB |
| 3800 MHz | 4900 MHz | | | > 33 dB |

Physical Specification

| | | | |
|---------------------|---------------------|-----------------------------|-----------------------------|
| Input Ports: | 1 | Min. Operating Temperature: | -35 °C |
| Output Ports: | 2 | Max. Operating Temperature: | 85 °C |
| Subtype: | Directional Coupler | Compliance/Certifications: | ISO 9001 Quality Management |
| Ingress Protection: | IP67 | | |
| Dimensions: | 159 x 72 x 22 mm | | |
| Weight: | 0.38 kg | | |

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

