

CommScope Directional Coupler, 20 dB, 555-6000 MHz, 4.3-10 Female, -165 dBc

SKU: ACC-CS-00023

MPN: C-20-UW-43-A16

Description

The CommScope Directional Coupler (SKU: ACC-CS-00023, Part Number: C-20-UW-43-A16) is a high-performance RF passive component designed for efficient signal distribution. Operating within a frequency range of 555-6000 MHz, this coupler provides a coupling value of 20 dB. It features a robust IP67-rated design, ensuring durability in harsh environments, and operates efficiently in temperatures from -35 °C to 85 °C.

Key electrical specifications include a 3rd Order PIM rating of -165 dBc and a standard input impedance of 50 Ω. The coupler offers a VSWR of 1.3:1 for frequencies 4900-6000 MHz, with insertion loss at 0.30 dB and inter-port isolation >30 dB. For frequencies 555-2700 MHz, the VSWR is 1.2:1 with isolation >35 dB. Between 3800-4900 MHz, it maintains a VSWR of 1.3:1 and isolation >36 dB, and for 2700-3800 MHz, the isolation exceeds 38 dB.

Equipped with 4.3-10 Female connectors on the input, output, and coupled ports, it meets ISO...

[Read More](#)



CommScope

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Specification

Min. Frequency:	555 MHz	Input Impedance:	50
Max. Frequency:	6000 MHz	Max. Input Power:	300 W
Coupling / Split:	20 dB	PIM, 3rd Order:	-165 dBc

Port Matrix

Port Function	RF Interface
Input	4.3-10 Female
Output	4.3-10 Female
Coupled	4.3-10 Female

Frequency Test Data

Start Frequency	Stop Frequency	VSWR	Insertion Loss	Inter-Port Iso.
4900 MHz	6000 MHz	< 1.3:1	0.3 dB	> 30 dB
555 MHz	2700 MHz	< 1.2:1		> 35 dB
3800 MHz	4900 MHz	< 1.3:1		> 36 dB
2700 MHz	3800 MHz	< 1.25:1		> 38 dB

Physical Specification

Input Ports:	1	Min. Operating Temperature:	-35 °C
Output Ports:	2	Max. Operating Temperature:	85 °C
Subtype:	Directional Coupler	Compliance/Certifications:	ISO 9001 Quality Management
Ingress Protection:	IP67	RoHS	
Dimensions:	159 by 72 by 22		
Weight:	0.38 kg		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

