

CommScope 2-Way Low PIM 4.3-10 Female High Power Splitter, 555-6000 MHz

SKU: ACC-CS-00030

MPN: S-2-UW-H-43-I6

Description

The CommScope 2-Way Low PIM High Power Splitter (SKU: ACC-CS-00030, Part Number: S-2-UW-H-43-I6) is designed for robust RF applications, operating across a frequency range of 555 MHz to 6000 MHz. This splitter features a 4.3-10 Female connector on both input and output ports, ensuring compatibility and ease of installation in network setups. With a coupling value of 3.00 dB, it supports efficient signal division while maintaining high performance with a 3rd Order PIM rating of -165 dBc and an input impedance of 50 Ω .

The splitter is built to endure harsh environments, boasting an IP67 ingress protection rating and an operational temperature range from -25 °C to 85 °C. Between 555 and 2700 MHz, it delivers a VSWR of less than 1.3:1, a return loss of ≤ 19.10 dB, and an insertion loss of 0.20 dB. From 2700 to 6000 MHz, the insertion loss is 0.30 dB. It complies with ISO 9001 and RoHS standards, ensuring quality and environmental...

[Read More](#)



COMMSCOPE®

CommScope

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Specification

Min. Frequency:	555 MHz	Input Impedance:	50
Max. Frequency:	6000 MHz	Max. Input Power:	300 W
Coupling / Split:	3 dB	PIM, 3rd Order:	-165 dBc

Port Matrix

Port Function	RF Interface
Input	4.3-10 Female
Output	4.3-10 Female

Frequency Test Data

Start Frequency	Stop Frequency	VSWR	Insertion Loss	Return Loss
555 MHz	2700 MHz	< 1.25:1	0.2 dB	≤ 19.1 dB
2700 MHz	6000 MHz		0.3 dB	

Physical Specification

Input Ports:	1	Min. Operating Temperature:	-25 °C
Output Ports:	2	Max. Operating Temperature:	85 °C
Subtype:	Power Divider	Compliance/Certifications:	ISO 9001 Quality Management
Ingress Protection:	IP67	RoHS	
Dimensions:	269 x 66 x 25 mm		
Weight:	0.42 kg		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

