

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

# **CommScope AVA5-50FX, HELIAX(r) Andrew Virtual Air(tm) Coaxial Cable, corrugated copper, 7/8 in, black PE jacket - 500m**

SKU  
ACC-CS-00015  
MPN  
AVA5-50FX

## Description

The CommScope AVA5-50FX is a high-performance 7/8-inch corrugated coaxial cable, designed for demanding applications in large antenna systems, including Distributed Antenna Systems (DAS), UHF, and cellular base stations. This cable features a solid corrugated copper outer conductor, providing 110 dB shielding effectiveness and low Passive Intermodulation (PIM) targets, ensuring superior signal integrity.

Measuring 500 metres and weighing 205 kilograms, this cable is built to endure multiple mating cycles and operates effectively across a frequency range of 1 GHz to 5000 GHz. It delivers excellent performance with a Voltage Standing Wave Ratio (VSWR) of  $\leq 1.13:1$  and Return Loss of  $\leq 24.30$  dB at various frequency points, including 680 MHz, 800 MHz, 960 MHz, 1700 MHz, and 2200 MHz.

Encased in a durable black PE jacket, the AVA5-50FX is compliant with ISO 9001 Quality Management and RoHS standards, reflecting its commitment to quality and...

[Read More](#)





## [CommScope](#)

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

## RF Specification

Start Frequency

1 GHz

Stop Frequency

5000 GHz

VSWR Measurement

Frequency	VSWR	Return Loss
-----------	------	-------------

680 MHz	$\leq 1.13:1$	$\leq 24.3$ dB
---------	---------------	----------------

800 MHz	$\leq 1.13:1$	$\leq 24.3$ dB
---------	---------------	----------------

1700 MHz	$\leq 1.13:1$	$\leq 24.3$ dB
----------	---------------	----------------

## Physical Specification

Subtype

[Cable Reel](#)

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Length  
500 m  
Weight  
410 g

## **AVA5-50FX**

Min. Frequency  
0 GHz  
Impedance  
50  $\Omega$   
Min. Bend Radius Static  
127 mm  
Min. Bend Radius Dynamic  
254 mm  
Max. Frequency  
5 GHz  
Colour  
Black  
Weight (g/m)  
410 g  
Cable Layers

<b>Layer</b>	<b>Diameter</b>	<b>Materials</b>
Inner Conductor	9.45 mm	<a href="#">Copper Tube</a>
Dielectric	24.13 mm	<a href="#">Foamed Polyethylene (EPE)</a>
Outer Conductor	25.40 mm	<a href="#">Corrugated Copper Tube</a>
Outer Jacket	27.99 mm	<a href="#">Polyethylene (PE)</a>

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

