

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

CommScope 3m 1/2" Jumper Cable with 4.3-10 Male to 4.3-10 Male Connectors

SKU
ACC-CS-00056
MPN
F4-HMHM-3M-P

Description

The CommScope 3m 1/2" Jumper Cable (SKU: ACC-CS-00056, Part Number: F4-HM3M-P) features 4.3-10 Male to 4.3-10 Male Connectors and is part of the RSJ4-50 series, renowned for its exceptional flexibility. This superflexible 1/2-inch foam coaxial cable, part of the HELIAX® range, is engineered with a corrugated copper outer conductor and a robust black polyethylene jacket, making it ideal for installations requiring tight bends and complex routing where space is limited.

The cable operates within a frequency range of 1 GHz to 4 GHz and boasts a 3rd Order PIM rating of -119 dBc, ensuring reliable performance. Its connectors are straight and free-hanging, allowing for easy installation. Performance measurements reveal a VSWR of $\leq 1.07:1$ and a Return Loss of ≤ 30.04 dB at 698 MHz and 1700 MHz, and a VSWR of $\leq 1.22:1$ with a Return Loss of ≤ 20.01 dB at 3400 MHz.

This cable assembly is compliant with ISO 9001 Quality Management and RoHS...

[Read More](#)





[CommScope](#)

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Specification

Start Frequency

0.7 GHz

PIM, 3rd Order

-119 dBc

Stop Frequency

3.8 GHz

VSWR Measurement

Frequency	VSWR	Return Loss
-----------	------	-------------

698 MHz	$\leq 1.07:1$	≤ 30.04 dB
---------	---------------	-----------------

1700 MHz	$\leq 1.07:1$	≤ 30.04 dB
----------	---------------	-----------------

2200 MHz	$\leq 1.08:1$	≤ 27.99 dB
----------	---------------	-----------------

3400 MHz	$\leq 1.22:1$	≤ 20.01 dB
----------	---------------	-----------------

Physical Specification

Subtype

[Jumper Cable](#)

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Length

3 m

RF Connectors

RF Interface Body Shape Mounting

[4.3-10 Male](#) [Straight](#) [Free Hanging](#)

[4.3-10 Male](#) [Straight](#) [Free Hanging](#)

[RSJ4-50](#)

Min. Frequency

0 GHz

Impedance

50 Ω

Min. Bend Radius Static

31.75 mm

Min. Bend Radius Dynamic

31.75 mm

Max. Frequency

10.2 GHz

Colour

Black

Weight (g/m)

150 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	3.59 mm	Copper Clad Aluminium (CCA)
Dielectric	9.42 mm	Foamed Polyethylene (EPE)
Outer Conductor	11.99 mm	Corrugated Copper Tube
Outer Jacket	13.41 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual

property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

