

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

CommScope 5m 1/2" Jumper Cable with 4.3-10 Male to 4.3-10 Male Connectors

SKU: ACC-CS-00058 MPN: F4-HMHM-5M-P

Description

The CommScope 5m 1/2" Jumper Cable (SKU: ACC-CS-00058) features 4.3-10 Male connectors on both ends, ideal for RF applications requiring flexibility and reliability. Part of the HELIAX® RSJ4-50 series, this superflexible coaxial cable is designed for installations demanding tight bends and space efficiency. Its construction includes a corrugated copper outer conductor and a durable black polyethylene jacket, making it suitable for complex routing without compromising performance.

With an operating frequency range of 1 GHz to 4 GHz, the cable maintains a 3rd Order PIM rating of -119 dBc and supports multiple mating cycles. It offers excellent performance with a VSWR of \leq 1.07:1 and a Return Loss of \leq 30.04 dB at 698 MHz and 1700 MHz, and VSWR of \leq 1.08:1 at 2200 MHz, ensuring minimal signal reflection and loss.

This cable assembly is compliant with ISO 9001 Quality Management and RoHS standards, ensuring high quality and environmental...

Read More



CommScope

COMMSCOPE®

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Specification

Start Frequency:	0.7 GHz	Stop Frequency:	3.8 GHz	
PIM, 3rd Order:	-119 dBc			

VSWR Measurement

Frequency	VSWR	Return Loss
698 MHz	≤ 1.07:1	≤ 30.04 dB
1700 MHz	≤ 1.07:1	≤ 30.04 dB
2200 MHz	≤ 1.08:1	≤ 27.99 dB
3400 MHz	≤ 1.22:1	≤ 20.01 dB

Physical Specification

Subtype:	Jumper Cable	Length:	5 m
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS	,		

RF Connectors

RF Interface	Body Shape	Mounting
4.3-10 Male	Straight	Free Hanging
4.3-10 Male	Straight	Free Hanging

RSJ4-50

Min. Frequency:	0 GHz	Max. Frequency:	10.2 GHz
Impedance:	50	Colour:	Black
Min. Bend Radius Static:	31.75 mm	Weight (g/m):	150 g
Min. Bend Radius Dynamic:	31.75 mm		

Cable Layers

Layer	Diameter	Materials
Inner Conductor	3.59 mm	Copper Clad Aluminium (CCA)
Dielectric	9.42 mm	Foamed Polyethylene (EPE)
Outer Conductor	11.99 mm	Corrugated Copper Tube
Outer Jacket	13.41 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

