

# CommScope FSJ4-50B SureFlex(r) Jumper with interface types N Male and N Male, 3.5 m

SKU: ACC-CS-00068

MPN: F4A-PNMNM-3M5

## Description

The CommScope FSJ4-50B SureFlex Jumper (SKU: ACC-CS-00068, Part No: F4A-PNMNM-3M5) is a high-performance RF coaxial cable measuring 3.5 metres. Designed for robust integration into large antenna systems, it features a 1/2" corrugated construction with a 15.87 mm outer diameter and a 4.83 mm inner conductor. Its solid corrugated copper outer conductor ensures 110 dB of shielding effectiveness, meeting low PIM targets crucial for superior signal integrity.

This cable is equipped with N Male connectors on both ends, one with a straight body and the other with a right-angle body, both free hanging for versatile installation. It supports a wide operating frequency range and is built to endure frequent mating cycles, making it ideal for passive Distributed Antenna Systems.

Performance metrics include a VSWR of  $\leq 1.11:1$  and a Return Loss of  $\leq 25.96$  dB at 3000 MHz, and a VSWR of  $\leq 1.08:1$  with a Return Loss of  $\leq 27.99$  dB at 2700 MHz. Compliant...

[Read More](#)



## RF Specification

Start Frequency:	0 GHz	Stop Frequency:	2.7 GHz
<b>COMMSCOPE®</b> VSWR Measurement			
<b>Frequency</b>		<b>VSWR</b>	<b>Return Loss</b>
3000 MHz		$\leq 1.11:1$	$\leq 25.96$ dB
2700 MHz		$\leq 1.08:1$	$\leq 27.99$ dB

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all

# Physical Specification

Subtype:	Jumper Cable	Length:	3.5 m
----------	--------------	---------	-------

Compliance/Certifications:	ISO 9001 Quality Management
----------------------------	-----------------------------

## RF Connectors

### RF Interface

N Male

7/16 DIN Male

### Body Shape

Straight

Right Angle

### Mounting

Free Hanging

Free Hanging

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

