Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

SMA Female Connector for L-240 Coaxial Cable, Bulkhead Rear Mount

SKU
ACC-PT-00188
MPN
SA2-C-L24-BRM
Barcode
9337692003516

Description

SMA connectors are a mainstay of low frequency wireless technologies.

This bulkhead mounted SMA Female connector is designed for an ordinary crimp and solder attachment to LMR-240 and equivalent series coaxial cables.

Installation is simple. After preparing the cable, the pin is soldered onto the centre conductor and outer body pushed over the top until the pin sits flush. A standard 6.5 mm (0.255") hex die is used to crimp the ferrule.

Read More

The bulkhead interface allows the SMA connector to be panel mounted by drilling a 7 mm diameter hole and sliding the body from the rear through the hole. The supplied nut and washer secures the SMA connector to the mounting surface.

Read More



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Connector Interface

RF Interface	Body Shape	Mounting
SMA Female	Straight	Bulkhead

RF Specification

Start Frequency
0 GHz
Stop Frequency
6 GHz
Input Impedance
50 Ω
Inner Contact Resistance
≤ 3 mΩ
Insulation Resistance
≥ 5000 mΩ
Outer Contact Resistance
≤ 2 mΩ
RF Operating Voltage
≤ 480 Vrms
VSWR Measurement

Frequency	VSWR
3000 MHz	≤ 1.2:1
6000 MHz	≤ 1.3:1

Physical Specification

Cable Group
L-240
Body Material
Brass
Body Plating
Gold
Insulator Material
PTFE / Teflon
Dimensions
22.5 × 9 × 9
Weight
5.7 g
Compliance/Certifications
ISO 9001 Quality Management
,
RoHS
Conductor Attachment
Cable, Crimp
Contact Material
Brass
Contact Plating
Gold
Min. Operating Temperature
-40 °C
Max. Operating Temperature
85 °C
Mating Cycles
> 500
Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

