

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

CommScope RSJ4-50 SureFlex(r) Jumper with interface types N Male and N Male, 0.5m

SKU
ACC-CS-00094
MPN
F4S-NMNM-M5-P

Description

The CommScope RSJ4-50 SureFlex Jumper Cable, model F4S-NMNM-M5-P, is a high-performance RF coaxial cable featuring N Male to N Male connectors. Measuring 0.5 metres and weighing 150 grams, this cable is constructed from 1/2" corrugated coaxial material, known for its reliability in large antenna systems and DAS applications.

Key features include a solid corrugated copper outer conductor offering 110 dB shielding, ensuring low PIM levels with a 3rd Order PIM rating of -112 dBc. It operates effectively within a frequency range of 1 GHz to 3 GHz, suitable for various networking needs. The cable's durability supports multiple mating cycles, ideal for dynamic environments.

Performance metrics at 960 MHz and 2200 MHz show a VSWR of $\leq 1.07:1$ and Return Loss of ≤ 30.04 dB, while at 2700 MHz, it maintains a VSWR of $\leq 1.11:1$ and Return Loss of ≤ 25.96 dB. These specifications underscore its capability for consistent signal transmission.

This product...

[Read More](#)



COMMScope®

[CommScope](#)

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Specification

PIM, 3rd Order

-112 dBc

VSWR Measurement

Frequency	VSWR	Return Loss
-----------	------	-------------

698 MHz	$\leq 1.07:1$	≤ 30.04 dB
---------	---------------	-----------------

1700 MHz	$\leq 1.07:1$	≤ 30.04 dB
----------	---------------	-----------------

2200 MHz	$\leq 1.11:1$	≤ 25.96 dB
----------	---------------	-----------------

Physical Specification

Subtype

[Jumper Cable](#)

Compliance/Certifications

[ISO 9001 Quality Management](#)

Length

0.5 m

RF Connectors

RF Interface	Body Shape	Mounting
--------------	------------	----------

N Male		
------------------------	--	--

	Straight	
--	--------------------------	--

		Free Hanging
--	--	------------------------------

N Male		
------------------------	--	--

	Straight	
--	--------------------------	--

		Free Hanging
--	--	------------------------------

[RSJ4-50](#)

Min. Frequency

0 GHz

Impedance

50 Ω

Min. Bend Radius Static

31.75 mm

Min. Bend Radius Dynamic

31.75 mm

Max. Frequency

10.2 GHz

Colour

Black

Weight (g/m)

150 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	3.59 mm	Copper Clad Aluminium (CCA)
Dielectric	9.42 mm	Foamed Polyethylene (EPE)
Outer Conductor	11.99 mm	Corrugated Copper Tube
Outer Jacket	13.41 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

