

CommScope HELIAX 1/2" SureFlex Jumper with interface types N Male and N Male, 1 m

SKU: ACC-CS-00111

MPN: F4A-PNMNM-1M

Description

The CommScope HELIAX 1/2" SureFlex Jumper (SKU: ACC-CS-00111, Part Number: F4A-PNMNM-1M) is a high-performance RF coaxial cable designed for demanding antenna systems. Featuring N Male connectors on both ends, this 1 m cable is crafted for seamless integration in passive Distributed Antenna Systems.

Constructed from a 1/2" corrugated coaxial cable, it boasts a 15.87 mm outer diameter and a 4.83 mm inner conductor. The solid corrugated copper outer conductor provides 110 dB of shielding, ensuring low passive intermodulation (PIM) and reliable performance. The cable is durable, designed to endure multiple mating cycles, and operates effectively across a 0-3000 GHz frequency range.

The SureFlex Jumper meets ISO 9001 quality management standards, affirming its high-quality construction. At 3000 MHz, it delivers a VSWR of $\leq 1.11:1$ and a return loss of ≤ 25.96 dB, while at 2700 MHz, it achieves a VSWR of $\leq 1.08:1$ and a return loss of ≤ 27.99 dB...

[Read More](#)



RF Specification

VSWR Measurement Frequency	CommScope	VSWR	Return Loss
3000 MHz	CommScope (NASDAQ: COMM) design, build and manage wired and wireless networks around the world. As a	$\leq 1.11:1$	≤ 25.96 dB
2700 MHz	regions of the world to anticipate what's next and push the boundaries of ...	$\leq 1.08:1$	≤ 27.99 dB

Physical Specification

Subtype:	Jumper Cable	Length:	1 m
----------	--------------	---------	-----

Compliance/Certifications:	ISO 9001 Quality Management
----------------------------	-----------------------------

RF Connectors

RF Interface

N Male

N Male

Body Shape

Straight

Straight

Mounting

Free Hanging

Free Hanging

RSJ4-50

Min. Frequency:	0 GHz	Max. Frequency:	10.2 GHz
-----------------	-------	-----------------	----------

Impedance:	50	Colour:	Black
------------	----	---------	-------

Min. Bend Radius Static:	31.75 mm	Weight (g/m):	150 g
--------------------------	----------	---------------	-------

Min. Bend Radius Dynamic:	31.75 mm
---------------------------	----------

Cable Layers

Layer	Diameter	Materials
Inner Conductor	3.59 mm	Copper Clad Aluminium (CCA)
Dielectric	9.42 mm	Foamed Polyethylene (EPE)
Outer Conductor	11.99 mm	Corrugated Copper Tube
Outer Jacket	13.41 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

