Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

CommScope HELIAX 1/2" SureFlex Jumper with interface types N Male and N Male, 1 m

SKU
ACC-CS-00111
MPN
F4A-PNMNM-1M

Description

The CommScope HELIAX 1/2" SureFlex Jumper (SKU: ACC-CS-00111, Part Number: F4A-PNMNM-1M) is a high-performance RF coaxial cable designed for demanding antenna systems. Featuring N Male connectors on both ends, this 1 m cable is crafted for seamless integration in passive Distributed Antenna Systems.

Constructed from a 1/2" corrugated coaxial cable, it boasts a 15.87 mm outer diameter and a 4.83 mm inner conductor. The solid corrugated copper outer conductor provides 110 dB of shielding, ensuring low passive intermodulation (PIM) and reliable performance. The cable is durable, designed to endure multiple mating cycles, and operates effectively across a 0-3000 GHz frequency range.

The SureFlex Jumper meets ISO 9001 quality management standards, affirming its high-quality construction. At 3000 MHz, it delivers a VSWR of ≤ 1.11:1 and a return loss of ≤ 25.96 dB, while at 2700 MHz, it achieves a VSWR of ≤ 1.08:1 and a return loss of ≤ 27.99 dB...

Read More



CommScope

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what’s next and push the boundaries of ...

RF Specification

VSWR Measurement

Frequency	VSWR	Return Loss
3000 MHz	≤ 1.11:1	≤ 25.96 dB
2700 MHz	≤ 1.08:1	≤ 27.99 dB

Physical Specification

Subtype
Jumper Cable
Compliance/Certifications
ISO 9001 Quality Management
Length
1 m
RF Connectors

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
N Male	Straight	Free Hanging

RSJ4-50

Min. Frequency
0 GHz
Impedance
50 Ω
Min. Bend Radius Static
31.75 mm
Min. Bend Radius Dynamic
31.75 mm
Max. Frequency
10.2 GHz
Colour
Black
Weight (g/m)
150 g
Cable Layers

Layer	Diameter	Materials
Inner Conductor	3.59 mm	Copper Clad Aluminium (CCA)
Dielectric	9.42 mm	Foamed Polyethylene (EPE)
Outer Conductor	11.99 mm	Corrugated Copper Tube
Outer Jacket	13.41 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

