

Commscope HELIAX 1/2" SureFlex Jumper Cable, N Male to N Male, 2.0m

SKU: ACC-CS-00377

MPN: F4A-HPNMNM-2M

Description

The Commscope HELIAX 1/2" SureFlex Jumper Cable, N Male to N Male (2.0m) is a premium RF cable designed for high-performance antenna systems. Model F4A-HPNMNM-2M features 1/2" corrugated coaxial construction, ideal for passive Distributed Antenna Systems. Its solid corrugated copper outer conductor ensures superior shielding with 110 dB effectiveness and meets low PIM targets, achieving a 3rd Order PIM rating of -112 dBc.

Designed for durability, this cable supports multiple mating cycles and operates efficiently across a frequency range of 680 MHz to 2700 MHz. The cable exhibits excellent performance with a VSWR of $\leq 1.07:1$ and Return Loss of ≤ 30.04 dB at 680 MHz and 1700 MHz, and a VSWR of $\leq 1.11:1$ at 2200 MHz. Both ends are fitted with N Male connectors, featuring a Straight body shape and Free Hanging mounting style.

Manufactured by CommScope, a global leader in communications infrastructure, this cable meets ISO 9001 quality...

[Read More](#)



COMMSCOPE®

CommScope

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of ...

RF Specification

Start Frequency:	0.68 GHz	Stop Frequency:	2.7 GHz
PIM, 3rd Order:	-112 dBc		

VSWR Measurement

Frequency	VSWR	Return Loss
680 MHz	≤ 1.07:1	≤ 30.04 dB
1700 MHz	≤ 1.07:1	≤ 30.04 dB
2200 MHz	≤ 1.11:1	≤ 25.96 dB

Physical Specification

Subtype:	Jumper Cable	Length:	2 m
Compliance/Certifications:	ISO 9001 Quality Management		

RF Connectors

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
N Male	Straight	Free Hanging

RSJ4-50

Min. Frequency:	0 GHz	Max. Frequency:	10.2 GHz
Impedance:	50	Colour:	Black
Min. Bend Radius Static:	31.75 mm	Weight (g/m):	150 g
Min. Bend Radius Dynamic:	31.75 mm		

Cable Layers

Layer	Diameter	Materials
Inner Conductor	3.59 mm	Copper Clad Aluminium (CCA)
Dielectric	9.42 mm	Foamed Polyethylene (EPE)
Outer Conductor	11.99 mm	Corrugated Copper Tube
Outer Jacket	13.41 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

