

# SMA Male Straight Solder Connector for RG-402 Cable

SKU: ACC-PT-00389  
 MPN: SA1-S-402  
 Barcode: 9337692004957

## Description

SMA solder connectors are used within high performance radio communications systems, such as in 4G and 5G cellular, microwave, mmWave, and aerospace applications.

This connector is used to terminate Semi-Flexible and Semi-Rigid 0.141" cable types such as RG-402, where both the inner conductor and outer braid are soldered to the connector.

As a low-PIM design the connector uses ternary alloys and silver plating to achieve very low VSWR under 3 GHz, and a modest < 1.3:1 VSWR up to 6 GHz.

This SMA Male coaxial connector is used in high performance and general-precision systems up to 6 GHz. Termination of semi-flexible cables, particularly those operating to 6 GHz must be made with great care and precision.

[Read More](#)

[RF Connector Interface](#)



RF Interface	Body Shape	Mounting
SMA Male	Straight	Free Hanging

## RF Specification

Powertec



Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	$\leq 1 \text{ m}\Omega$
		Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 1 \text{ m}\Omega$
		RF Operating Voltage:	$\leq 260 \text{ Vrms}$

#### VSWR Measurement


Frequency	VSWR
6000 MHz	$\leq 1.2:1$

## Physical Specification

Cable Group:	RG-402	Conductor Attachment:	Cable, Solder
Body Material:	Brass	Contact Material:	Brass
Body Plating:	Gold	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	$-65 \text{ }^\circ\text{C}$
Dimensions:	$13 \times 7.8 \times 7.8$	Max. Operating Temperature:	$165 \text{ }^\circ\text{C}$
Weight:	3 g	Mating Cycles:	> 500
Compliance/Certifications:	ISO 9001 Quality Management		

RoHS

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

