

# Poynting CAB-118, 5x 5m HDF-195 Low Loss Cables for 5-in-1 Antennas

SKU: ANT-PY-00038  
 MPN: CAB-118

## Description

The Poynting CAB-118 is a set of five 5m HDF-195 low-loss cables designed for 5-in-1 antennas, part number ANT-PY-00038. These coaxial jumper cables utilise the L-195 series, known for their high performance as a robust alternative to RG-58, RG-122, RG-303, and RG-142. The L-195 features a double-shielded outer conductor that ensures superior RF shielding of over 90 dB and a PE jacket that guarantees more than 20 years of service life. Each cable supports an operating frequency range from 0 to 6000 GHz, with a VSWR of  $\leq 1.35:1$  at 6000 MHz, offering reliable performance for various applications.

The cables are equipped with an SMA Female connector on one end and an RP-SMA Male connector on the other, both with a straight body and free-hanging mounting style. These connectors are designed to endure frequent mating cycles, making them ideal for demanding environments. The CAB-118 cables are CE and RoHS compliant, ensuring they meet...

[Read More](#)



## RF Specification

Start Frequency:	0 GHz	Stop Frequency:	6 GHz
VSWR Measurement	Poynting		VSWR
	<b>Frequency</b>	Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and	
	6000 MHz		$\leq 1.35:1$
	PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...		

# Physical Specification

Subtype:	Feeder Cable	Length:	5 m
Compliance/Certifications:	CE		
RoHS			

## RF Connectors

RF Interface	Body Shape	Mounting
SMA Female	Straight	Free Hanging
SMA Male	Straight	Free Hanging
RP-SMA Male	Straight	Free Hanging

## L-195

Min. Frequency:	0 GHz	Max. Frequency:	41 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	12.7 mm	Colour:	Black
Min. Bend Radius Dynamic:	50.8 mm	Weight (g/m):	30 g
Attenuation @ 1 GHz:	0.39 dB/m		

## Cable Layers

Layer	Diameter	Materials	Notes
Inner Conductor	0.94 mm	Solid Copper	Some cable variants have a stranded inner conductor
Dielectric	2.79 mm	Foamed Polyethylene (EPE)	
Outer Conductor	2.95 mm	Aluminium Foil (Bonded)	
Outer Conductor	3.53 mm	Tinned Copper Braid (TC)	
Outer Jacket	4.95 mm	Polyethylene (PE)	

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

