

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

## N Male Connector for L-240 Cable, Right Angle

SKU: ACC-PT-00392 MPN: N1-C-L24

Barcode: 9337692004612

### Description

The N Male Connector for L-240 Cable, Right Angle (SKU: ACC-PT-00392) is engineered by Powertec, part number N1-C-L24, for a range of low-frequency applications like UHF, 4G LTE, and WiFi. This N-Type connector is renowned for its durability and excellent power handling capabilities.

Specifically designed for terminating LMR-240 or equivalent coaxial cables, this right-angled connector features a hexagonal coupling nut, facilitating easy tightening with a torque wrench. Installation is straightforward: after prepping the cable, the outer body is fitted over until the centre conductor aligns with the inner contact, requiring minimal soldering. The ferrule is crimped using a standard 6.5 mm hex die.

Constructed with a Brass body and Nickel plating, it features Gold-plated Brass inner contacts and a PTFE/Teflon insulator. It supports over 500 mating cycles and operates between -65 °C to 165 °C, with a frequency range up to 6.0 GHz. The...

Read More





#### Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## RF Connector Interface

RF Interface	Body Shape	Mounting
N Male	Right Angle	Free Hanging

# RF Specification


Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	≤ 1 mΩ
		Insulation Resistance:	≥ 5000 mΩ
		Outer Contact Resistance:	≤ 1 mΩ
		RF Operating Voltage:	≤ 500 Vrms

## **VSWR** Measurement

Frequency	VSWR
6000 MHz	≤ 1.35:1

# **Physical Specification**

Cable Group:	L-240	Conductor Attachment:	Cable, Crimp
Body Material:	Brass	Contact Material:	Brass
Body Plating:	Nickel	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-65 °C
Dimensions:	27.5 × 20 × 27.8	Max. Operating Temperature:	165 °C
Weight:	42.1 g	Mating Cycles:	> 500
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS	,		



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

