

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

## **Telegartner RG-214 Coax-Cable, 100+-1m Ring**

SKU  
ACC-TG-00016  
MPN  
100012857

### **Description**

The Telegärtner RG-214 Coaxial Cable (SKU: ACC-TG-00016) is a robust 50  $\Omega$  cable designed for high-frequency telecommunications, including broadcast, UHF, and military applications. With a length of 100 m and weighing 2.07 kg, this RG-214 cable offers superior performance compared to standard RG-213 cables, thanks to its large centre conductor and double shielding. These features ensure low attenuation and reliable operation up to 11 GHz.

This cable is engineered for durability, capable of withstanding multiple mating cycles, and meets RoHS compliance standards. Telegärtner, a renowned German brand established in 1945, has a strong reputation for producing high-tech telecommunications components. Their extensive experience and international presence highlight their commitment to quality and innovation in cable assembly and related technologies.

Choose the Telegärtner RG-214 for its enhanced frequency support, improved attenuation, and...

[Read More](#)



## Telegärtner

As family-owned company the Telegärtner Group has developed to an international network of affiliated companies specialising in intermediate and end products for telecommunications and data communications for customers with the most exacting demands for high-tech applications over the last 70 years.

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

## **RF Specification**

## **Physical Specification**

Subtype

[Cable Reel](#)

Compliance/Certifications

[RoHS](#)

Length

100 m

Weight

2073 g

### **RG-214**

Min. Frequency

0 GHz

Impedance

50  $\Omega$

Min. Bend Radius Static

40 mm

Attenuation @ 1 GHz

0.24 dB/m

Max. Frequency

11 GHz

Shielding Effectiveness

> 75 dB

Colour

Black

Weight (g/m)

207.3 g

Cable Layers

Layer	Diameter	Materials	Notes
Inner Conductor	2.25 mm	<a href="#">Silver Plated Copper (SC)</a>	7x0.75
Dielectric	7.24 mm	<a href="#">Polyethylene (PE)</a>	
Outer Conductor	7.90 mm	<a href="#">Silver Plated Copper Braid</a>	
Outer Conductor	8.50 mm	<a href="#">Silver Plated Copper Braid</a>	
Outer Jacket	10.80 mm	<a href="#">Polyvinyl Chloride (PVC)</a>	

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

