

Telegärtner 4.3-10 straight jack, clamp/clamp, G24 (7/8"); G52 (7/8" Alu), SIMFix CA-Pro

SKU: ACC-TG-00012
MPN: 100025267

Description

The Telegärtner 4.3-10 Straight Jack is a high-performance RF connector designed for use with 7/8" corrugated cables, offering robust connectivity in telecommunications and data communications systems. Its straight body and free-hanging mounting style make it ideal for applications requiring durable, reliable connections in challenging environments. This connector is engineered to support a frequency range of 0 to 6.0 GHz, making it suitable for a variety of RF and microwave applications, including mobile communications, broadcast systems, and network infrastructure.

Constructed with a brass body and a copper-silver alloy plating, it ensures excellent conductivity and corrosion resistance, while the PTFE/Teflon insulator provides superior electrical insulation. Capable of withstanding over 500 mating cycles, it offers long-lasting performance even under frequent use. The connector maintains a low 3rd order PIM rating of ≤ -155 dBc...

[Read More](#)



Telegärtner

As family-owned company the Telegärtner Group has developed to an international network of affiliated companies specialising in intermediate and end products for telecommunications and data communications for customers with the most exacting demands for high-tech applications over the last 70 years.

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

RF Connector Interface

RF Interface

4.3-10 Female

Body Shape

Straight

Mounting

Free Hanging

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Inner Contact Resistance:	$\leq 1 \text{ m}\Omega$
PIM, 3rd Order:	$\leq -155 \text{ dBc}$	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 0.5 \text{ m}\Omega$
		RF Operating Voltage:	$\leq 2500 \text{ Vrms}$


VSWR Measurement

Frequency	Return Loss
2000 MHz	$\leq 36 \text{ dB}$
4000 MHz	$\leq 27 \text{ dB}$
6000 MHz	$\leq 25 \text{ dB}$

Physical Specification

Cable Group:	7/8 Corrugated	Conductor Attachment:	Cable, Captivated
Body Material:	Brass	Contact Material:	Brass, Copper Alloy
Body Plating:	Copper-Silver Alloy (Cu2Ag5 / Cu2Ag3)	Contact Plating:	Copper-Silver Alloy (Cu2Ag5 / Cu2Ag3)
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-40 °C
Dimensions:	66 x 36	Max. Operating Temperature:	85 °C
Weight:	140 g	Ingress Protection:	IP68
Compliance/Certifications:	RoHS	Mating Cycles:	> 500

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

