

Telegärtner N Straight Plug Crimp G1 (RG-58C/U) crimp/crimp

SKU: ACC-TG-00017
 MPN: 100023906

Description

The Telegärtner N Straight Plug Crimp G1 is a high-performance coaxial RF connector designed for professional telecommunications and data communications applications. This N Male connector features a straight body and a free-hanging mounting style, making it ideal for seamless integration with RG-58 cable types using a crimp attachment mechanism. Its robust construction from lead-brass alloy, with copper-silver alloy plating, ensures excellent durability and reliable connectivity.

Engineered to operate within a frequency range of 0 to 11 GHz, this connector is suitable for a wide array of RF applications, including wireless communication systems and antenna connections. It supports an impedance of 50 ohms, making it compatible with standard RF systems while maintaining signal integrity through low inner and outer contact resistance. The PTFE/Teflon insulator provides excellent thermal stability, allowing the connector to function in...

[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging

RF Specification Telegärtner



As family-owned company the Telegärtner Group has developed to an international network of affiliated companies specialising in intermediate and end products for telecommunications and data communications for customers with the most exacting demands for high-tech applications over the last 70 years.

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	11 GHz	Inner Contact Resistance:	≤ 1.5 mΩ
		Insulation Resistance:	≥ 5000 mΩ
		Outer Contact Resistance:	≤ 1 mΩ


VSWR Measurement

Frequency	Return Loss
1000 MHz	≤ 34 dB
2000 MHz	≤ 29 dB
4000 MHz	≤ 25 dB
11000 MHz	≤ 24 dB

Physical Specification

Cable Group:	RG-58	Conductor Attachment:	Cable, Crimp
Body Material:	Lead-Brass Alloy (CuZn39Pb3)	Contact Material:	Lead-Brass Alloy (CuZn39Pb3)
Body Plating:	CuSnZn3	Contact Plating:	Copper-Silver Alloy (Cu2Ag5 / Cu2Ag3)
Insulator Material:	PTFE / Teflon	Mating Cycles:	> 500
Dimensions:	32.8 x 20.8		
Compliance/Certifications:	RoHS		

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

