

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Telegartner N Straight Plug G21 (1/2") SIMFix Pro IP68

SKU
ACC-TG-00018
MPN
100023973

Description

The Telegärtner N Straight Plug G21 SIMFix Pro is a high-performance coaxial RF connector designed for robust telecommunications and data communications applications. As a N Male connector, it features a straight body shape ideal for free-hanging mounting, making it versatile for various installations. This connector is specifically engineered to attach seamlessly to 1/2" corrugated cable types. Constructed with a durable brass body and coated with CuSnZn3 plating, it ensures longevity and reliable performance. The inner contacts use a copper alloy with a copper-silver alloy plating, enhancing electrical conductivity.

This connector can handle over 500 mating cycles, making it suitable for demanding environments where frequent connections and disconnections are required. Operating within a temperature range of -40°C to 85°C and supporting frequencies from 0 GHz to 6 GHz, it is designed for a wide array of RF applications. The connector's...

[Read More](#)



Telegärtner

As family-owned company the Telegärtner Group has developed to an international network of affiliated companies specialising in intermediate and end products for telecommunications and data communications for customers with the most exacting demands for high-tech applications over the last 70 years.

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

RF Connector Interface

RF Interface Body Shape Mounting

[N Male](#)

[Straight](#)

[Free Hanging](#)

RF Specification

Start Frequency

0 GHz

Stop Frequency

6 GHz

PIM, 3rd Order

≤ -155 dBc

Input Impedance

50 Ω

Inner Contact Resistance

≤ 1.5 m Ω

Insulation Resistance

≥ 5000 m Ω

Outer Contact Resistance

≤ 1 mΩ

RF Operating Voltage

≤ 1000 Vrms

VSWR Measurement

Frequency Return Loss

2000 MHz ≤ 36 dB

4000 MHz ≤ 32 dB

6000 MHz ≤ 28 dB

Physical Specification

Cable Group

[1/2 Corrugated](#)

Body Material

[Brass](#)

Body Plating

[CuSnZn3](#)

Insulator Material

[Topas COC](#)

Dimensions

64 x 24.8

Compliance/Certifications

[RoHS](#)

Contact Material

[Copper Alloy](#)

Contact Plating

[Copper-Silver Alloy \(Cu₂Ag₅ / Cu₂Ag₃\)](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C


Ingress Protection

[IP68](#)

Mating Cycles

> 500

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

