

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# Telegartner N Straight Jack Crimp G1 (RG-58C/U) crimp/crimp

SKU: ACC-TG-00028 MPN: 100023999

#### Description

The Telegärtner N Straight Jack Crimp G1 (RG-58C/U) is a high-performance coaxial RF connector designed for reliable connectivity in telecommunications and data communications systems. Used predominantly in RF and microwave applications, this N Female connector is ideal for connecting RG-58 cable types, offering a robust and secure connection through its crimp attachment mechanism. Its straight body shape and free-hanging mounting style make it versatile for various installation scenarios, enhancing its utility in both intermediate and end-product telecommunications setups.

Constructed with a brass body and plated with CuSnZn3, alongside copper alloy inner contacts with copper-silver alloy plating, this connector ensures excellent conductivity and durability. The PTFE/Teflon insulator supports stable electrical performance across a broad frequency range, up to 4 GHz, with minimal signal loss. It delivers an impressive VSWR of ≤ 1.08:1...

Read More





#### Telegärtner

As family-owned company the Telegärtner Group has developed to an international network of affiliated companies specialising in intermediate and end products for telecommunications and data communications for customers with the most exacting demands for high-tech applications over the last 70 years.

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

#### RF Connector Interface


RF Interface	Body Shape	Mounting
N Female	Straight	Free Hanging

## RF Specification

# Frequency VSWR Insertion Loss 1000 MHz ≤ 1.04:1 0.1 dB 2000 MHz ≤ 1.05:1 0.1 dB 4000 MHz ≤ 1.08:1 0.1 dB

### **Physical Specification**

RG-58	Conductor Attachment:	Cable, Crimp
Brass	Contact Material:	Copper Alloy
CuSnZn3	Contact Plating:	Copper-Silver Alloy (Cu2Ag5 /
PTFE / Teflon		Cu2Ag3)
38.3 x 13		
	Brass CuSnZn3 PTFE / Teflon	Brass Contact Material:  CuSnZn3 Contact Plating:  PTFE / Teflon



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

