

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Telegartner N Straight Jack Crimp G37 (9913 Belden) crimp/crimp

SKU
ACC-TG-00030
MPN
100024015

Description

The Telegärtner N Straight Jack Crimp G37 (SKU: ACC-TG-00030, Part No. 100024015) is an RF connector designed for superior performance in demanding applications. This N Female connector features a straight, free-hanging design, compatible with RG-8 cables via a crimp attachment. With dimensions of 42.6 x 12.5 mm, it is lightweight and robust, constructed from a lead-brass alloy with copper-silver plating to ensure durability and excellent conductivity. The inner contacts also utilise a copper-silver plated brass for optimal signal transmission, and the PTFE/Teflon insulator provides reliable electrical isolation.

Operating within a frequency range of 0 to 4.0 GHz, this connector is engineered for stability, with an input impedance of 50 Ω . It meets RoHS compliance standards, ensuring environmental safety. The connector delivers outstanding performance, with a return loss of ≤ 34.00 dB and an insertion loss of 0.10 dB at 1000 MHz...

[Read More](#)



Telegärtner

As family-owned company the Telegärtner Group has developed to an international network of affiliated companies specialising in intermediate and end products for telecommunications and data communications for customers with the most exacting demands for high-tech applications over the last 70 years.

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

RF Connector Interface

RF Interface Body Shape Mounting

[N Female](#) [Straight](#) [Free Hanging](#)

RF Specification

Start Frequency

0 GHz

Stop Frequency

4 GHz

Input Impedance

50 Ω

VSWR Measurement

Frequency Return Loss Insertion Loss

1000 MHz	≤ 34 dB	0.1 dB
2000 MHz	≤ 30.5 dB	0.1 dB
3000 MHz	≤ 28 dB	0.1 dB

Physical Specification

Cable Group

[RG-8](#)

Body Material

[Lead-Brass Alloy \(CuZn39Pb3\)](#)

Body Plating

[Copper-Silver Alloy \(Cu2Ag5 / Cu2Ag3\)](#)

Insulator Material

[PTFE / Teflon](#)

Dimensions

42.6 x 12.5

Compliance/Certifications

[RoHS](#)

Conductor Attachment

[Cable, Crimp](#)


Contact Material

[Brass](#)

Contact Plating

[Copper-Silver Alloy \(Cu2Ag5 / Cu2Ag3\)](#)

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

