

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

## Telegartner N bulkhead jack crimp G37 crimp/crimp

SKU: ACC-TG-00037 MPN: 100024030

#### Description

The Telegärtner N Bulkhead Jack Crimp (Model: 100024030, SKU: ACC-TG-00037) is a high-performance RF connector, ideal for telecommunications and data communications applications. This N Female connector features a straight body and bulkhead front mount, designed for use with L-400 cable types. Its crimp/crimp attachment ensures secure and efficient connections.

Constructed with a robust Copper-Nickel-Lead-Phosphorus body and Copper-Silver Alloy plating, the connector offers durability and excellent conductivity. The inner contacts are similarly plated, while the PTFE/Teflon insulator provides reliable electrical isolation. This connector supports a standard input impedance of 50  $\Omega$  and is RoHS compliant, ensuring environmental safety.

Engineered for resilience, it is rated for numerous mating cycles and operates across a wide temperature range, making it versatile for various environments. Its performance at key frequencies is noteworthy...

Read More





#### Telegärtner

As family-owned company the Telegärtner Group has developed to an international network of affiliated companies specialising in intermediate and end products for telecommunications and data communications for customers with the most exacting demands for high-tech applications over the last 70 years.

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

## RF Connector Interface

RF Interface	Body Shape	Mounting
N Female	Straight	Bulkhead

# RF Specification


Start Frequency:	0 GHz	Input Impedance:	50	
Stop Frequency:	4 GHz			

### VSWR Measurement

1000 MHz ≤ 34 dB 0.1 dB 2000 MHz ≤ 30.5 dB 3000 MHz ≤ 28 dB	Frequency	Return Loss	Insertion Loss
	1000 MHz	≤ 34 dB	0.1 dB
3000 MHz ≤ 28 dB	2000 MHz	≤ 30.5 dB	
	3000 MHz	≤ 28 dB	

# **Physical Specification**

Cable Group:	L-400	Conductor Attachment:	Cable, Crimp
<u> </u>			·
Body Material:	Lead-Brass Alloy (CuZn39Pb3)	Contact Material:	Copper-Nickel-Lead- Phosphorus (CuNi1Pb1P)
Body Plating:	CuSnZn3	Contact Plating:	Copper-Silver Alloy (Cu2Ag5 /
Insulator Material:	PTFE / Teflon		Cu2Ag3)
Dimensions:	42.7 x 19		
Compliance/Certifications:	RoHS		



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

