

# CommScope APT-HFHM Quarterwave Surge Arrestor 695-2700 MHz, 4.3-10 Female to 4.3-10 Male

SKU: ACC-CS-00072  
 MPN: APT-HFHM

## Description

The CommScope APT-HFHM Quarterwave Surge Arrestor (SKU: ACC-CS-00072) is a robust RF surge protector designed for superior protection in telecommunications networks. Operating within a frequency range of 695 to 2700 MHz, it offers reliable performance with 4.3-10 Female to 4.3-10 Male connectors. This component is engineered to endure over 100 mating cycles and functions efficiently in extreme temperatures from -45 °C to 85 °C.

With an input impedance of 50 Ω and an impulse discharge current rating of 10 kA (8/20 waveform), this surge protector ensures optimal circuit protection. It achieves a 3rd Order PIM rating of -117 dBc, maintaining signal integrity. The device is IP68 rated, guaranteeing excellent protection against dust and water ingress, and it complies with ISO 9001 and IEC 60529 standards for quality and mechanical reliability.

Performance metrics include a VSWR of ≤ 1.25:1 at 695 MHz and ≤ 1.15:1 at 2170 MHz, with minimal...


[Read More](#)

RF Connector Interface



RF Interface	Body Shape	Mounting
4.3-10 Female	Straight	Free Hanging
4.3-10 Male	Straight	Free Hanging

CommScope



## RF Specification

CommScope (NASDAQ: COMM) helps design, build and manage wired and wireless networks around the world. As a communications infrastructure leader, we shape the always-on networks of tomorrow. For more than 40 years, our global team of greater than 20,000 employees, innovators and technologists have empowered customers in all regions of the world to anticipate what's next and push the boundaries of

Start Frequency:	0.7 GHz	Input Impedance:	50
Stop Frequency:	2.7 GHz	Impulse Discharge:	10 kA (8/20 waveform)
PIM, 3rd Order:	-117 dBc		

VSWR Measurement

Frequency	VSWR	Return Loss	Insertion Loss
695 MHz	≤ 1.25:1	≤ 19.1 dB	0.08 dB
806 MHz	≤ 1.13:1	≤ 24.3 dB	
2170 MHz	≤ 1.15:1	≤ 23.13 dB	

## Physical Specification

Body Plating:	White Bronze	Contact Plating:	Silver
Dimensions:	73 x 25 x 97	Min. Operating Temperature:	-45 °C
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	85 °C
		Mating Cycles:	> 100
		Ingress Protection:	IP68
		Mechanical Compliance:	IEC 60529: IP Code

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

