Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

2J Phoenix 4G-5G WiFi Ultraband 2x2 MIMO Stud Antenna, 617 to 5925 MHz

SKU
ANT-2J-00017
MPN
2J6983BA

Description

The 2J Phoenix 4G-5G WiFi Ultraband 2x2 MIMO Stud Antenna (SKU: ANT-2J-00017, Part Number: 2J6983BA) offers robust wireless connectivity across frequencies from 617 to 5925 MHz. This IP67-rated antenna ensures reliable performance in harsh conditions, with an operating temperature range from -40 °C to 85 °C. Designed for versatility, this Fin/Stud/Combo antenna supports 2x2 MIMO technology, enhancing data throughput and signal quality through its dual RF connections.

Each antenna element features a 50 Ω impedance and can handle up to 25 W input power. Linear polarisation facilitates consistent signal reception, making it ideal for applications in automotive, marine, telematics, and M2M markets. The antenna's RF performance across various frequency bands is characterised by peak gains ranging from 2.0 dBi to 5.1 dBi and VSWR values under 3.3:1, ensuring efficient energy transmission.

Connectivity is achieved via dual SMA Male interfaces...

Read More



2J

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

Cable 1: 5GNR

Start Frequency
617 MHz
Stop Frequency
5925 MHz
Max. Input Power
25 W
Polarisation
Linear
Input Impedance
50 Ω
RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	L-100	300 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Avg. Gain	Efficiency

617 MHz	960 MHz	2.1 dBi	> 11.2 dB	< 2:1	-3.5 dBi	46%
1427 MHz	2690 MHz	2.1 dBi	> 8.3 dB	< 2.6:1	-3.1 dBi	51%
3300 MHz	5000 MHz	3.8 dBi	> 7.1 dB	< 3.2:1	-5.1 dBi	33%
5150 MHz	5925 MHz	3.9 dBi	> 7.4 dB	< 2.6:1	-5.2 dBi	31%

Cable 2: 5GNR

Start Frequency
617 MHz
Stop Frequency
5925 MHz
Max. Input Power
25 W
Polarisation
Linear
Input Impedance
50 Ω
RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	L-100	300 mm


Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Avg. Gain	Efficiency
617 MHz	960 MHz	3.2 dBi	> 9.6 dB	< 2.1:1	-3.7 dBi	45%
1427 MHz	2690 MHz	2 dBi	> 8.2 dB	< 2.6:1	-3 dBi	52%
3300 MHz	5000 MHz	5.1 dBi	> 6.9 dB	< 3.3:1	-4.3 dBi	40%
5150 MHz	5925 MHz	4.7 dBi	> 7 dB	< 2.8:1	-4.9 dBi	34%

Physical Specification

Subtype
Fin / Stud / Combo
Input Ports
2
MIMO
2x2 MIMO
Min. Operating Temperature
-40 °C
Max. Operating Temperature
85 °C

Dimensions
80 x 74 x 25.6
Ingress Protection
IP67
Compliance/Certifications
RoHS
Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE

LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

