

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

## N Male Connector for L-240 Coaxial Cable

SKU: ACC-PT-00040 MPN: N1-C-L24

Barcode: 9337692000935


#### Description

The N Male Connector for L-240 Coaxial Cable (SKU: ACC-PT-00040), part number N1-C-L24, is engineered by Powertec for reliable performance in RF applications including UHF, 3G, 4G LTE, and WiFi. Known for its durability and power handling, this N-Type connector is ideal for terminating LMR-240 or equivalent braided coaxial cables.

Featuring a straightforward installation process, the pin is soldered to the centre conductor, and the outer body is secured over it until flush. The ferrule is crimped using a standard 6.5 mm (.255") hex die. This straight body connector with a free-hanging mounting style is constructed from nickel-plated brass, with gold-plated brass inner contacts, and a PTFE insulator, ensuring robust performance.

With dimensions of 26.0 × 19.0 × 9.1 mm, it operates at frequencies from 0 GHz to 6.0 GHz, maintaining an input impedance of 50  $\Omega$  and insulation resistance of  $\geq$  5000 m $\Omega$ . The connector can handle RF operating...

Read More





#### Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## RF Connector Interface

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging

# RF Specification


Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Insulation Resistance:	≥ 5000 mΩ
Dielectric Withstand:	1500 Vrms	RF Operating Voltage:	≤ 1000 Vrms

### **VSWR** Measurement

Frequency	VSWR
6000 MHz	≤ 1.5:1

# **Physical Specification**

Cable Group:	L-240	Conductor Attachment:	Cable, Crimp
Body Material:	Brass	Contact Material:	Brass
Body Plating:	Nickel	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-55 °C
Dimensions:	26.0 × 19.0 × 9.1	Max. Operating Temperature:	165 °C
Compliance/Certifications:	RoHS	Mating Cycles:	> 500



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

