

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

ZCG WiFi 2.4 GHz High Gain Vehicle Spring Mount Antenna, 2400 to 2500 MHz, 8 dBi, 5m RP-SMA Male

SKU: ACC-ZC-00061 MPN: SG2400-8

Description

The ZCG WiFi 2.4 GHz High Gain Vehicle Spring Mount Antenna (SKU: ACC-ZC-00061) is a robust and reliable solution for enhancing wireless connectivity in vehicles. Operating within the 2400 to 2500 MHz frequency range, this collinear antenna delivers a peak gain of 8 dBi, ideal for applications requiring extended range and improved signal strength. Constructed from durable fibreglass (GRP), it ensures longevity and resilience in various environmental conditions.

Designed by ZCG Scalar, an esteemed Australian manufacturer with decades of expertise in RF solutions, this antenna is vertically polarised and supports up to 10 W of input power, making it suitable for demanding communication needs. Its 50 Ω impedance and VSWR of less than 2.0:1 ensure optimal performance and efficiency.

The antenna features a 5-metre RP-SMA Male cable, offering flexibility in installation. With a 360° azimuth beamwidth and a 17° elevation beamwidth, it provides...

Read More



ZCG Scalar

ZCG Scalar™ is a world class radio frequency antenna designer, manufacturer and consulting organisation that offer an integrated approach to identifying RF solutions in partnership with client needs.

ZCG Scalar™ is an Australian owned business operating since 1970. We manufacture hundreds of antenna models to suit your RF communication and broadcasting requirements. The design and development of ...

RF Specification

Start Frequency:	2400 MHz	Polarisation:	Vertical (V)
Stop Frequency:	2500 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

PortsRF InterfaceLength1RP-SMA Male5000 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation
2400 MHz	2500 MHz	8 dBi	< 2:1	360°	17°

Physical Specification

Subtype:	Collinear	Materials:	Fibreglass (GRP)
Input Ports:	1		
MIMO:	1x1 SISO		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

