

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

## **N Male Four-Hole Flange Connector with Round Post**

SKU  
N1-4F-RP001  
MPN  
N1-RP-4F

### **Description**

N (or N-Type) flange connectors are used within high performance low-band radio communications systems, such as in aerospace, radar, 4G cellular, and broadcast.

This connector is used to terminate coaxial cable types onto a panel where both the inner conductor and outer braid are soldered accordingly. The connector body has a flange design with four mounting holes.

As a low-PIM design the connector uses ternary alloys to achieve very low VSWR under 3 GHz, and a modest  $< 1.3:1$  VSWR up to 6 GHz.

This N Male coaxial connector is used in high performance and general-precision systems up to 6 GHz. Termination of flange connectors particularly those operating towards the upper frequency limit must be made with great care and precision.

[Read More](#)





## [Powertec](#)

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## RF Connector Interface

### RF Interface Body Shape Mounting

[N Male](#)

[Straight](#)

[4-Hole Flange](#)

## RF Specification

Start Frequency

0 GHz

Stop Frequency

4 GHz

Input Impedance

50  $\Omega$

Inner Contact Resistance

$\leq 1 \text{ m}\Omega$

Insulation Resistance

$\geq 5000 \text{ m}\Omega$

Outer Contact Resistance

$\leq 1 \text{ m}\Omega$

RF Operating Voltage

$\leq 500$  Vrms

VSWR Measurement

**Frequency VSWR**

4000 MHz  $\leq 1.3:1$

## Physical Specification

Body Material

[Brass](#)

Body Plating

[Nickel](#)

Insulator Material

[PTFE / Teflon](#)

Dimensions

27.3 × 25.4 × 25.4

Weight

44.5 g

Compliance/Certifications

[ISO 9001 Quality Management](#)

,

[RoHS](#)

Conductor Attachment

[Round Post](#)

Contact Material

[Beryllium Copper](#)

Contact Plating

[White Bronze](#)

Min. Operating Temperature

-40 °C


Max. Operating Temperature

85 °C

Mating Cycles

> 500

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

