

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

2J I-Bar 4G-5G WiFi Ultraband Adhesive Antenna, 617 to 5925 MHz

SKU
ANT-2J-00010
MPN
2J5083P

Description

The 2J I-Bar 4G-5G WiFi Ultraband Adhesive Antenna (SKU: ANT-2J-00010) offers robust performance across a wide frequency range of 617 to 5925 MHz. Crafted from durable polycarbonate and ABS plastic, this compact adhesive patch antenna is designed to withstand extreme temperatures from -40 °C to 85 °C, making it suitable for various challenging environments.

With a 1x1 SISO configuration and a linear polarisation, this antenna supports a 50 Ω impedance and handles up to 35 W of input power. Its RF performance covers multiple frequency bands, making it ideal for diverse applications. Whether in automotive, marine, telematics, or M2M markets, this antenna provides reliable connectivity. The antenna features a single SMA Male interface with a straight connector body, connected via a 300 mm L-100 cable, ensuring easy integration into existing systems.

Meeting RoHS compliance standards, the 2J I-Bar antenna is not only high-performing but also...

[Read More](#)





[2J](#)

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

Start Frequency

617 MHz

Stop Frequency

5925 MHz

Max. Input Power

35 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape Cable Series Length

1	SMA Male	Straight	L-100	3000 mm
---	--------------------------	--------------------------	-----------------------	---------

Frequency Test Data

Start Freq. Stop Freq. Peak Gain Return Loss VSWR Efficiency

617 MHz	960 MHz	3.2 dBi	> 15.3 dB	< 1.5:1	60%
1427 MHz	2690 MHz	3.6 dBi	> 12.8 dB	< 1.7:1	46%

Start Freq. Stop Freq. Peak Gain Return Loss VSWR Efficiency

3300 MHz	5000 MHz	1 dBi	> 12.1 dB	< 1.8:1	25%
5150 MHz	5925 MHz	1.6 dBi	> 15.6 dB	< 1.5:1	25%

Physical Specification

Subtype

[Adhesive Patch](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

116 x 22 x 6.7

Materials

[ABS Plastic](#), [Polycarbonate \(PC\)](#)

Mounting

[Adhesive](#)

Compliance/Certifications

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

