

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

2J Dual-Band WiFi Adhesive Antenna, 2410 to 5925 MHz

SKU
ANT-2J-00011
MPN
2J5502P

Description

The 2J Dual-Band WiFi Adhesive Antenna (SKU: ANT-2J-00011) is a high-performance solution designed for versatile connectivity across automotive, marine, telematics, automation, and M2M applications. Operating within the 2410 to 5925 MHz frequency range, this antenna ensures reliable dual-band WiFi connectivity. It features an adhesive patch design for easy installation and is constructed from durable ABS plastic, allowing it to withstand temperatures from -40 °C to 85 °C.

The antenna offers a single RF connection via an RP-SMA Male interface, supported by a 300 mm L-100 cable. Its linear polarisation and 50 Ω impedance make it suitable for a range of demanding environments. In the 2.4 GHz band, it achieves a peak gain of 3.4 dBi and a VSWR of less than 1.3:1, while in the 5 GHz band, it offers a peak gain of 2.6 dBi with a VSWR of less than 1.9:1. The antenna's 360° azimuth beamwidth ensures comprehensive coverage, with radiated...

[Read More](#)





[2J](#)

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

Cable 1: 2.4/5.0 GHz ISM

Start Frequency

2410 MHz

Stop Frequency

5925 MHz

Max. Input Power

25 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

1	RP-SMA Male	Straight	L-100	3000 mm
---	-----------------------------	--------------------------	-----------------------	---------

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Azimuth	Avg. Gain	Efficiency
2410 MHz	2490 MHz	3.4 dBi	> 18.1 dB	< 1.31:1	360°	-2.5 dBi	57%
4920 MHz	5925 MHz	2.6 dBi	> 11.2 dB	< 1.91:1	360°	-4.7 dBi	34%

Physical Specification

Subtype

[Adhesive Patch](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

71 x 25 x 7

Materials

[ABS Plastic](#)

Mounting

[Adhesive](#)

Compliance/Certifications

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

