

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

## **2J 868-915 MHz LPWAN Adhesive Antenna, 863 to 928 MHz**

SKU  
ANT-2J-00012  
MPN  
2J5515P

### **Description**

The 2J 868-915 MHz LPWAN Adhesive Antenna (SKU: ANT-2J-00012) is a compact and efficient solution designed for reliable performance in the 863 to 928 MHz frequency range. Developed by 2J, this adhesive patch antenna is crafted from durable ASA plastic and measures 71 x 25 x 7 mm, making it ideal for space-constrained environments. It operates effectively in extreme temperatures from -40 °C to 85 °C, ensuring versatility across various applications.

This antenna is well-suited for automotive, M2M, base station, and embedded system applications, offering seamless integration with a 1x SMA Male RF connection via a 3000 mm RG-174 cable. It features a linear polarisation with a 50  $\Omega$  impedance, supporting up to 25 W of input power. The antenna demonstrates a peak gain of 3.3 dBi and 2.8 dBi within its respective frequency ranges, maintaining a 360° azimuth beamwidth and a consistent radiated efficiency of 32%.

2J, a Slovakian brand, is renowned...

[Read More](#)





## [2J](#)

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

## RF Specification

### Cable 1: 868/915 MHz

Start Frequency

863 MHz

Stop Frequency

928 MHz

Max. Input Power

25 W

Polarisation

[Linear](#)

Input Impedance

50  $\Omega$

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

1	<a href="#">SMA Male</a>	<a href="#">Straight</a>	<a href="#">RG-174</a>	3000 mm
---	--------------------------	--------------------------	------------------------	---------

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Azimuth	Avg. Gain	Efficiency
863 MHz	870 MHz	3.3 dBi	> 8.6 dB	< 2.2:1	360°	-5 dBi	32%
902 MHz	928 MHz	2.8 dBi	> 10.8 dB	< 1.8:1	360°	-5 dBi	32%

## Physical Specification

Subtype

[Adhesive Patch](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

71 x 25 x 7

Materials

[ASA Plastic](#)

Mounting

[Adhesive](#)

Compliance/Certifications

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

