

2J 915 MHz LPWAN Narrowband LP-Stud Antenna, 902 to 928 MHz

SKU: ANT-2J-00016

MPN: 2J6615B-915

Description

The 2J 915 MHz LPWAN Narrowband LP-Stud Antenna (SKU: ANT-2J-00016, Part Number: 2J6615B-915) is an advanced antenna solution designed by 2J, a renowned Slovakian brand known for its innovative antenna technologies. This Fin/Stud/Combo antenna operates within the 902 to 928 MHz frequency range, making it ideal for ISM band applications. With a 50Ω impedance and support for up to 25 W input power, it delivers reliable performance with a peak gain of 0.9 dBi and a VSWR of less than 1.5:1.

The antenna is constructed to withstand harsh environments, featuring an IP67 ingress protection rating and a broad operational temperature range from -40°C to 85°C , ensuring durability and consistent performance in demanding conditions. Its linear polarisation and compact size (77.3 x 15 mm) make it suitable for a variety of applications including automotive, M2M, base stations, and embedded systems.

2J's antennas are supported by a wealth of modern...

[Read More](#)



2J



2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

915 MHz ISM Antenna

Start Frequency:	902 MHz	Polarisation:	Linear
Stop Frequency:	928 MHz	Input Impedance:	50
Max. Input Power:	25 W		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	RG-174	3000 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Avg. Gain	Efficiency
902 MHz	928 MHz	0.85 dBi	> 13.5 dB	< 1.5:1	-4.7 dBi	34%

Physical Specification

Subtype:	Fin / Stud / Combo	Dimensions:	77.3 x 15
Input Ports:	1	Ingress Protection:	IP67
MIMO:	1x1 SISO	Materials:	Thermoplastic Elastomer (TPE), ZAMAK
Min. Operating Temperature:	-40 °C	Mounting:	Stud / Bulkhead / Panel
Max. Operating Temperature:	85 °C	Compliance/Certifications:	RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

