

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

2J 4G-5G WiFi Ultraband 4x4 MIMO + GNSS 5-Port Combo Stud Antenna, 617 to 5925 MHz

SKU
ANT-2J-00026
MPN
2J7B84BGFC

Description

The 2J 4G-5G WiFi Ultraband 4x4 MIMO + GNSS 5-Port Combo Stud Antenna (SKU: ANT-2J-00026) is a versatile solution designed for diverse applications, including automotive, marine, and telematics. With its capability to operate across a broad frequency range of 617 to 5925 MHz, it supports 4x4 MIMO configurations, enhancing data throughput and connectivity reliability.

Constructed from durable ASA plastic, this antenna is IP67 rated, ensuring robust performance in challenging environments, withstanding temperatures from -40 °C to 85 °C. Its five RF connections include four SMA Male interfaces for 5G NR, each supporting up to 35 W input power with linear polarisation, and one dedicated GNSS port for GPS/GLONASS/QZSS/Galileo. The GNSS port features an active LNA with 24 dBic gain, ensuring precise location tracking.

2J, based in Slovakia, is renowned for its innovative antenna solutions, leveraging advanced engineering tools to meet customer...

[Read More](#)





[2J](#)

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

Cable 1: 5GNR

Start Frequency

617 MHz

Stop Frequency

5925 MHz

Max. Input Power

35 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

1	SMA Male	Straight	L-195	3000 mm
---	--------------------------	--------------------------	-----------------------	---------

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Avg. Gain	Efficiency
-------------	------------	-----------	-------------	------	-----------	------------

617 MHz	960 MHz	-1.3 dBi	> -5.6 dB	< 3.5:1 -5 dBi	-32%
1427 MHz	2690 MHz	-3.4 dBi	> -11.7 dB	< 1.9:1 -3.9 dBi	-41%
3300 MHz	5000 MHz	-4.8 dBi	> -15.2 dB	< 1.5:1 -3.8 dBi	-42%
5150 MHz	5925 MHz	-4 dBi	> -14.2 dB	< 1.6:1 -4.4 dBi	-37%

Cable 2: 5GNR

Start Frequency

617 MHz

Stop Frequency

5925 MHz

Max. Input Power

35 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape Cable Series Length

1 [SMA Male](#) [Straight](#) [L-195](#) 3000 mm

Frequency Test Data

Start Freq. Stop Freq. Peak Gain Return Loss VSWR Avg. Gain Efficiency

617 MHz	960 MHz	-1.2 dBi	> -6.2 dB	< 3.2:1 -5 dBi	-32%
1427 MHz	2690 MHz	-3.5 dBi	> -12.5 dB	< 1.9:1 -3.9 dBi	-41%
3300 MHz	5000 MHz	-4.6 dBi	> -15.1 dB	< 1.5:1 -3.7 dBi	-43%
5150 MHz	5925 MHz	-3.2 dBi	> -16 dB	< 1.5:1 -4.8 dBi	-33%

Cable 3: 5GNR

Start Frequency

617 MHz

Stop Frequency

5925 MHz

Max. Input Power

35 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape Cable Series Length

1 [SMA Male](#) [Straight](#) [L-195](#) 3000 mm

Frequency Test Data

Start Freq. Stop Freq. Peak Gain Return Loss VSWR Avg. Gain Efficiency

617 MHz	960 MHz	1.3 dBi	> 5.6 dB	< 3.7:1 -5 dBi	32%
1427 MHz	2690 MHz	3.8 dBi	> 12.8 dB	< 1.8:1 -3.8 dBi	42%
3300 MHz	5000 MHz	4.5 dBi	> 16.7 dB	< 1.4:1 -4 dBi	40%
5150 MHz	5925 MHz	4.6 dBi	> 12.4 dB	< 1.8:1 -4.2 dBi	39%

Cable 4: 5GNR

Start Frequency

617 MHz

Stop Frequency

5925 MHz

Max. Input Power

35 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape Cable Series Length

1 [SMA Male](#) [Straight](#) [L-195](#) 3000 mm

Frequency Test Data

Start Freq. Stop Freq. Peak Gain Return Loss VSWR Avg. Gain Efficiency

617 MHz	960 MHz	1.7 dBi	> 5.9 dB	< 3.3:1 -5.1 dBi	31%
1427 MHz	2690 MHz	3.4 dBi	> 12.7 dB	< 1.8:1 -3.8 dBi	42%
3300 MHz	5000 MHz	4.6 dBi	> 16.8 dB	< 1.5:1 -3.7 dBi	43%
5150 MHz	5925 MHz	3.9 dBi	> 15.4 dB	< 1.5:1 -4.6 dBi	35%

Cable 5: GPS/GLONASS/QZSS/Galileo

Start Frequency

1575.42 MHz

Stop Frequency

1610 MHz

Input Impedance

50 Ω

Polarisation

[Right Hand Circular \(RHCP\)](#)

Low Noise Amplifier (LNA)

LNA Gain

24 dBic

Noise Figure

≤ 1.2 dB

Power Consumption

< 137.5 mW

Min. Operating Voltage

2.7 V

Max. Operating Voltage

5.5 V

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

1	SMA Male	Straight	L-100	3000 mm
---	--------------------------	--------------------------	-----------------------	---------

Physical Specification

Subtype

[Fin / Stud / Combo](#)

Input Ports

5

MIMO

[4x4 MIMO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

96 x 130

Ingress Protection

[IP67](#)

Materials

[ASA Plastic](#)

Mounting

[Stud / Bulkhead / Panel](#)

Compliance/Certifications

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

