

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

2J Dual-Band WiFi-6E Flexible Embedded Adhesive Antenna, 2410 to 7125 MHz

SKU
ANT-2J-00028
MPN
2JF0102PA

Description

The 2J Dual-Band WiFi-6E Flexible Embedded Adhesive Antenna (SKU: ANT-2J-00028) offers advanced connectivity for a range of applications in automotive, telematics, and M2M markets. Designed by 2J, a leading Slovakian antenna manufacturer, this PCB/Surface Mount antenna provides robust performance across the 2410 MHz to 7125 MHz frequency range, making it ideal for WiFi 6E networks.

With a compact size of 67.5 x 25.0 x 0.2 mm and the ability to operate in temperatures from -40 °C to 85 °C, it is well-suited for diverse environments. The antenna's linear polarisation and 50 Ω impedance ensure optimal signal integrity, supporting up to 25 W of input power. Featuring a single RF connection via a U.FL Female interface with a 100 mm cable, it simplifies integration into various systems.

This antenna excels in providing consistent performance with peak gains of up to 4.7 dBi and radiated efficiency reaching 71% across its operating bands. Its...

[Read More](#)





[2J](#)

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

WiFi 6E

Start Frequency

2410 MHz

Stop Frequency

7125 MHz

Max. Input Power

25 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

1	U.FL Female	Straight	1.37 mm Mini-Coax	100 mm
---	-----------------------------	--------------------------	-----------------------------------	--------

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Azimuth	Avg. Gain	Efficiency
2410 MHz	2490 MHz	2 dBi	> 22.1 dB	< 1.21:1	360°	-1.5 dBi	71%
4920 MHz	5925 MHz	4.7 dBi	> 14.6 dB	< 1.51:1	360°	-1.7 dBi	68%
5925 MHz	7125 MHz	3.7 dBi	> 8.8 dB	< 2.21:1	360°	-2.3 dBi	59%

Physical Specification

Subtype

[Adhesive Patch](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

67.5 x 25.0 x 0.2

Materials

[Plastic](#)

Mounting

[Adhesive](#)

Compliance/Certifications

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

