POWERTEC | DATASHEET | UNCONTROLLED WHEN PRINTED PUBLIC | August 9, 2025 02:58

Page



Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# 2J 868-915 MHz LPWAN Flexible Embedded Adhesive Antenna, 863 to 928 MHz

SKU ANT-2J-00029 MPN 2JF0415P

#### Description

The 2J 868-915 MHz LPWAN Flexible Embedded Adhesive Antenna (SKU: ANT-2J-00029) is a versatile PCB/surface mount antenna designed for robust performance across the 863 to 928 MHz frequency range. With its compact dimensions of 25 x 70 x 0.2 mm, this antenna is an ideal solution for spaceconstrained applications. Its construction allows for operation in extreme temperatures from -40 °C to 85 °C, making it suitable for diverse environments.

This antenna features a single input port with a U.FL female interface connected via a 100 mm mini-coax cable, ensuring reliable connectivity. It supports up to 25 W of input power and maintains a 50  $\Omega$  impedance, offering linear polarisation for enhanced signal integrity. The antenna performs efficiently with a peak gain of 2.7 dBi and 3.6 dBi across different frequency ranges, achieving radiated efficiency of up to 77%.

Engineered by 2J, a leader in antenna solutions, this product is RoHS compliant and...

Read More



# **J**2J

#### **2**J

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

## **RF** Specification

#### Cable 1: 868/915 MHz ISM

Start Frequency 863 MHz Stop Frequency 928 MHz Max. Input Power 25 W Polarisation Linear Input Impedance 50 Ω **RF** Connectors Ports RF Interface Body Shape Cable Series Length 1 U.FL Female Straight 1.37 mm Mini-Coax 100 mm Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Azimuth	Avg. Gain	Efficiency
863 MHz	870 MHz	2.7 dBi	> 8 dB	< 2.3:1	360°	-2.3 dBi	58%
902 MHz	928 MHz	3.6 dBi	> 21 dB	< 1.2:1	360°	-1.1 dBi	77%

### **Physical Specification**

Subtype PCB / Surface Mount Input Ports 1 MIMO 1x1 SISO Min. Operating Temperature -40 °C Max. Operating Temperature 85 °C **Dimensions** 25 x 70 x 0.2 Materials Plastic Mounting Adhesive **Compliance/Certifications** RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

