

2J Brick 5G NR/4G LTE/3G/2G High-Performance Mini Embedded Surface Mount Antenna

SKU: ANT-2J-00031

MPN: 2JE71

Description

The 2J Brick Mini Embedded Surface Mount Antenna (SKU: ANT-2J-00031) is a versatile, high-performance solution designed for seamless integration into 5G NR, 4G LTE, 3G, and 2G applications. Manufactured by 2J, this PCB-type antenna features a compact design with dimensions of 40 x 8 x 3 mm and is constructed from durable fibreglass (GRP), ensuring reliability in demanding environments ranging from -40°C to 105°C.

Engineered for efficiency, the antenna operates across a broad frequency spectrum of 617 MHz to 5925 MHz with a 50 Ω impedance and supports up to 25 W of input power. Its linear polarisation and SISO configuration optimise connectivity for applications in automotive, marine, telematics, automation, and M2M markets. The antenna's robust RF performance, characterised by various gain and efficiency metrics, makes it suitable for a wide array of telecommunication needs.

Compliant with RoHS standards, the 2J Brick antenna is ideal for...

[Read More](#)



RF Specification

2J PCB Surface Mount

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

Start Frequency: 617 MHz Polarisation: Linear

Stop Frequency: 5925 MHz Input Impedance: 50

Max. Input Power: 25 W

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Avg. Gain	Efficiency
617 MHz	960 MHz	0.5 dBi	> 6.7 dB	< 3.1:1	-2.8 dBi	55%
1427 MHz	2690 MHz	2.7 dBi	> 10.3 dB	< 2:1	-2.2 dBi	61%
3300 MHz	5000 MHz	3.1 dBi	> 10.2 dB	< 2:1	-2.4 dBi	60%
5150 MHz	5925 MHz	2.2 dBi	> 5.7 dB	< 3.5:1	-4.2 dBi	40%

Physical Specification

Subtype:	PCB / Surface Mount	Dimensions:	40 x 8 x 3
MIMO:	1x1 SISO	Materials:	Fibreglass (GRP)
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	RoHS
Max. Operating Temperature:	105 °C		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

