

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

2J 915 MHz LPWAN Narrowband Dipole Antenna, 902 to 928 MHz

SKU: ANT-2J-00032 MPN: 2J2115B-915-B05H

Description

The 2J 915 MHz LPWAN Narrowband Dipole Antenna, model 2J2115B-915-B05H, is designed for optimal performance within the 902 to 928 MHz frequency range, making it ideal for ISM applications. Constructed with durable ASA plastic, brass, and stainless steel, it boasts an IP67 ingress protection rating, ensuring reliable operation in harsh environments. The antenna's linear polarisation and 50 Ω impedance support up to 25 W input power, making it suitable for diverse applications such as automotive, M2M, and base stations.

Featuring a peak gain of 3.1 dBi, a VSWR of less than 1.9:1, and 71% radiated efficiency, this single-input antenna delivers robust performance. Its 360° azimuth beamwidth ensures comprehensive coverage, while the average gain of -1.8 dBi highlights its stable performance. The antenna is equipped with an SMA male interface and a 3000 mm RG-58 cable, facilitating easy integration into existing systems.



Read More





2]

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

915 MHz ISM Antenna

Start Frequency:	902 MHz	Polarisation:	Linear
Stop Frequency:	928 MHz	Input Impedance:	50
Max. Input Power:	25 W		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	RG-58	3000 mm

Frequency Test Data

Start Freq. St	top Freq. F	Peak Gain	Return Loss	VSWR	Azimuth	Avg. Gain	Efficiency
902 MHz 92	28 MHz	3.1 dBi	> 10.9 dB	< 1.9:1	360°	-1.8 dBi	71%

Physical Specification

Subtype:	Dipole	Dimensions:	325 x 36 x 155 (220 x 16)	
Input Ports:	1	Ingress Protection:	IP67	
MIMO:	1x1 SISO	Materials:	ASA Plastic, Brass, Stainless	
Min. Operating Temperature:	-40 °C	Mounting	Steel (303) Wall / Vertical Surface	
Max. Operating Temperature:	85 °C	Mounting:		
		Compliance/Certifications:	RoHS	

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

