POWERTEC | DATASHEET | UNCONTROLLED WHEN PRINTED PUBLIC | August 8, 2025 19:00

Page



Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

2J Dual-Band WiFi Adhesive Antenna, 2410 to 5925 MHz, TNC Male, 3m

SKU ANT-2J-00037 MPN 2J5502P-300LL100-C118NYST CU022737

Description

The 2J Dual-Band WiFi Adhesive Antenna (ANT-2J-00037) is designed for seamless connectivity across 2.4 GHz and 5.0 GHz frequency bands, making it ideal for automotive, M2M, base station, and embedded applications. With a compact size of 71 x 25 x 7 mm, this adhesive patch antenna is fabricated from durable ABS plastic, ensuring reliability in harsh environments with an operating temperature range of -40 °C to 85 °C.

Engineered for optimal RF performance, the antenna features a 1x1 SISO configuration with a 50 Ω impedance and supports up to 25 W input power. It offers a peak gain of 3.4 dBi in the 2410-2490 MHz band and 2.6 dBi in the 4920-5925 MHz band. Its linear polarisation and RP-SMA Male interface, connected via a 3m cable, ensure robust signal transmission.

2J, a leader in antenna solutions, utilises state-of-the-art engineering tools to deliver high-quality products tailored to specific customer requirements. The company's...

Read More



J2J

2J

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

2.4/5.0 GHz ISM Antenna

Start Frequency 2410 MHz Stop Frequency 5925 MHz Max. Input Power 25 W Polarisation Linear Input Impedance 50 Ω RF Connectors **Ports RF Interface Cable Series Length** 1 RP-SMA Male L-100 3000 mm

Frequency Test Data

Start Freq. Stop Freq. Peak Gain Return Loss VSWR Avg. Gain Efficiency

2410 MHz	2490 MHz	3.4 dBi	> 18.1 dB	< 1.3:1 -2.5 dBi	57%
4920 MHz	5925 MHz	2.6 dBi	> 11.2 dB	< 1.9:1 -4.7 dBi	34%

Physical Specification

Subtype **Adhesive Patch** Input Ports 1 ΜΙΜΟ 1x1 SISO Min. Operating Temperature -40 °C Max. Operating Temperature 85 °C Dimensions 71 x 25 x 7 Materials **ABS Plastic** Mounting Adhesive **Compliance/Certifications** RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

