

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

2J 3G-5G Low Profile Magnetic Whip Antenna, 617 to 5925 MHz, SMA Male, 3m

SKU
ANT-2J-00038
MPN
S1304100729

Description

The 2J 3G-5G Low Profile Magnetic Whip Antenna (SKU: ANT-2J-00038) is a versatile solution designed for broad telecommunication applications, offering coverage from 617 to 5925 MHz. Engineered with a robust build of brass and polypropylene, it delivers reliable performance across extreme temperatures ranging from -40 °C to 85 °C. This antenna is equipped with a single SMA Male connector and a 3-metre cable, ensuring easy integration into various systems.

With a linear polarisation and 50 Ω impedance, this whip antenna efficiently supports up to 35 W of input power. Its design caters to a wide range of applications including automotive, M2M, base stations, and embedded systems, making it ideal for both standard and custom installations. The antenna's omnidirectional azimuth beamwidth of 360° ensures comprehensive signal coverage.

2J, a Slovakian leader in antenna technology, provides innovative solutions for markets such as automotive...

[Read More](#)





[2J](#)

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...

RF Specification

5G NR Antenna

Start Frequency

617 MHz

Stop Frequency

5925 MHz

Max. Input Power

35 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

1	SMA Male	Straight	L-100	3000 mm
---	--------------------------	--------------------------	-----------------------	---------

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Azimuth	Avg. Gain	Efficiency
617 MHz	960 MHz	1 dBi	> 11.5 dB	< 1.8:1	360°	-2.2 dBi	61%
1427 MHz	2690 MHz	2.9 dBi	> 10.4 dB	< 1.9:1	360°	-2.6 dBi	55%
3300 MHz	5000 MHz	2.5 dBi	> 7.4 dB	< 2.6:1	360°	-5.7 dBi	28%
5150 MHz	5925 MHz	-0.4 dBi	> 6.6 dB	< 2.8:1	360°	-6.4 dBi	23%

Physical Specification

Subtype

[Whip](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

31 x 109

Materials

[Brass](#), [Polypropylene \(PP\)](#)

Compliance/Certifications

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

